PO Box 14527, Wadeville 1422 562 Crocker Road Wadeville, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



# **TECHNICAL DATA SHEET Lube X Penetrating Spray**

### PRODUCT DESCRIPTION

Extreme performance, silicone-based, reinforced, release spray, Lubex penetrating spray is a powerful release agent for corroded threaded fasteners and other seized components. Penetrating spray has unique properties not shown by conventional mineral oil. Lubex penetrating spray incorporates corrosion inhibitors to provide a protective film against further attack after use.

#### **APPLICATIONS**

- Corroded threaded fasteners.
- Seized components.
- Outdoor and marine environments.
- General industrial applications.

## **BENEFITS**

Lubex penetrating spray provides excellent penetration in seized or corroded fasteners even after prolonged periods of seizure. It provides efficient loosening of fasteners when seized due to rust, scale, dirt, grime etc. it is dispensed via a powerful jet spray which mechanically penetrates rust and debris. The fast-acting formulation of Lubex penetrating spray minimizes time and effort when dealing with seized fasteners. Fasteners generally seize again once they start moving. Lubex penetrating spray has a high repellence property, less viscous and highly penetrating to aid dismantling of components.

## **DIRECTIONS FOR USE**

Shake the aerosol well before use. Test compatibility with plastics and rubbers and painted or coated surfaces prior to application. Hold the can upright and apply from 15 - 30cm, coating the components thoroughly and paying attention to the seized contact areas. In severe cases, applying of Lubex penetrating spray for a second time after several minutes may be beneficial. Use only in well ventilated areas and do not apply to very hot surfaces. Store below +50°C, out of direct sunlight. Shelf life is 5 years from date of manufacture. Consult safety data sheet before use.

PACKAGE SIZE	6 x 300g	24 x 300g
Lube X Penetrating Spray	1	<b>\</b>



