


PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Blixem Lamp Oil

1. PRODUCT AND COMPANY IDENTIFICATION

Trade Name	Blixem Lamp Oil
Manufacturer/Supplier	OILFLOW cc P.O.Box 14527 562 Crocker Road, Wadeville, Germiston, South Africa 1422
Phone Number	(011) 827-5848
Fax Number	(011) 827-5832
Oilflow Website:	www.oilflow.co.za

2. HAZARDS IDENTIFICATION.

Product is classified as hazardous according to Schedules 1 to 6 of the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001 of the HSNO Act, 1996.

HSNO Classifications: 3.1C, 6.1E, 6.3B

Signal word **WARNING**

Hazard Statement:

P102 Keep out of reach of children

P103 Read label before use

P210 Keep away from heat, open flames, hot surfaces. No smoking

P233 Keep container tightly close

P241 Use explosion proof electrical/ventilating/lighting equipment

P242 Use only non-sparking tools

3. INFORMATION ON HAZARDOUS INGREDIENTS

Naphtha petroleum distillates	64741-65-7	30 - 60
Light Distillates	64742-47-8	30 - 60



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Blixem Lamp Oil

4. FIRST AID MEASURES

For advice contact your local doctor with the label of the container at hand.

Swallowed

If swallowed, do not induce vomiting, rinse mouth and give water to sip, If vomiting persists, bend head closer to hips to avoid vomitus entry into lungs.

Skin Contact

If skin contact occurs, remove contaminated clothing and pass running water to affected skin.

Eye Contact

If splashed on eyes, hold the eyelids apart and pass running water for 15 minutes. If irritation occurs, contact the physician.

Inhalation

Retreat to get fresh air immediately. Seek medical attention if rapid recovery does not occur.

5. FIRE FIGHTING MEASURES

Flashpoint 38°C

Flammable limits LFL and UFL not determined.

Extinguishing media:

Foam, CO₂ or dry chemical . Use spray jets or water fog on large fires

Fire & Explosion hazards

Flammable liquids and vapour. The vapour forms explosive mixture with air. Do not breathe smoke

Firefighting Equipment:

Full protective clothing and self-contained breathing apparatus.

In the event of fire:

Notify the Fire Brigade, indicate location and nature of hazard.

Keep by-standers away


Wear breathing apparatus

Eliminate source of fire



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Blixem Lamp Oil

Switch off electrical hazard

Allow trained personnel to attend to the fire

Prevent product and extinguishing media from going into drains and waterways

Hazards from combustion products:

Product will emit toxic fumes of carbon dioxide

Hazchem Code 3Y

6. ACCIDENTAL RELEASES.

Emergency Procedures & Containment:

Refer to "Fire Fighting Measures" and "First Aid Measures "

Minor Spills

Clean up spill immediately

Remove all ignition sources

Wear protective clothes

Seal container and dispose of safely

Major Spills

Notify the Fire Brigade

Wear correct PPE

Contain spill with sand, saw dust

Use spark free shovels and explosion proof equipment


Prevent spill entry into drains, waterway and sewers

If entry into sewers occurs, notify Emergency department or the local authority.



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Blixem Lamp Oil

7. HANDLING AND STORAGE.

Precaution for safe handling:

Read product label before use. Use in well ventilated areas. smoking, hot surfaces or naked lights. Avoid generation of static electricity. Avoid all personal contact and inhalation. Wear correct PPE. Wash and with soap after handling.

Condition for safe handling.

Store in original package in a cool dry well-ventilated place. Keep out of reach of children. Check container periodically for leaks and or distortion.

Incompatible materials

Oxidising agents.

8. EXPOSURE CONTROLS: PERSONAL PROTECTION.

Health Exposure Standards :

Petroleum Distillates 165 ppm (1200 mg/m³)

Biological limits: None established

Engineering Controls:

Ventilation: Avoid breathing vapours, and use outdoors in well ventilated places

Personal Protective Equipment:

Respiratory Protection: Not normally required, use an SAA approved respirator in confined spaces

Eye Protection: Protect eyes from splashes with goggles or use safety glasses with side shields.

Skin or Body Protection: Wear PVC gloves, safety foot wear or gum boots.

9. PHYSICAL AND CHEMICAL PROPERTIES.

Property	Unit of measure	Typical value
Appearance	-	Clear liquid
Odour	-	Solvent
Flash Point	°C	38



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Blixem Lamp Oil

Density	kg/L	0.77
Vapour pressure	kPa	Not available
Explosive limits in air	%	Not available
Viscosity	cSt	Not available
Volatiles	%vol/vol	>99
Solubility in water	%w/w	Immiscible

10. STABILITY AND REACTIVITY.

Chemical Stability	Stable at room temperature and pressure
Condition to avoid	Contact with oxidising agents, nitrates, chlorine, bleach and pool HTH
Hazardous decomposition products	N/A

11. TOXICOLOGICAL INFORMATION.

Acute Effects

Ingestion: If swallowed may cause gastrointestinal tract discomfort, oedema and mucosal ulceration. Symptoms may be burning sensation of mouth and throat, also nausea, vomiting, feeling weak or dizzy. Vomiting may lead to aspiration into lungs and chemical pneumonitis.

Eye contact

Irritation of eyes, tearing and redness. Large splashing may lead to blurred visions and blindness.

Skin Contact

Irritation to the skin, defatting leading to dry and cracked skin and dermatitis.

Inhalation: This may lead to discomfort of the respiratory tract, drowsiness and dizziness and narcosis, lack of co-ordination.

Chronic Effects

Symptoms include dizziness, weakness, irritability, lack of concentration and memory loss


Other Health Effects: N/A

Toxicological Information:



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Blixem Lamp Oil

Dermal, LD₅₀. rat 4700mg/kg

Inhalation LC₅₀ (4hr) rat 3.1 mg/L

12. ECOLOGICAL INFORMATION.

Eco toxicity:

Aquatic toxicity: Classified as toxic to aquatic animals, however does not contain eco toxic ingredients

Persistence/Degradability: Not expected to be persistence or bio accumulative

Mobility: Product not miscible with water

Other Information: Citronella oil

Rainbow trout LC₅₀ (96hr) 17.3mg/kg

Daphna magna EC₅₀(48hr) 26.4mg/L

Environmental Exposure Standard: EEL_(WATER) EEL_(SOIL) EEL_(SEDIMENTS) have not been set yet.

13. DISPOSAL CONSIDERATIONS.

Disposal methods

Recycle empty containers through a reputable qualified or licensed contractor as packaging may still contain product vapour.

14. TRANSPORT INFORMATION.

UN Number: 1993

Shipping name: FLAMMABLE LIQUID. N.O.S

Class: 3

Packaging group: III

Hazchem Code: 3Y

Dangerous Goods Segregation

This product is classified as Dangerous Goods Class 3.

Please consult NZS 5433:2007 Transport of Dangerous Goods on Land information.



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Blixem Lamp Oil

15. REGULATORY INFORMATION.

Labelling according to EU guidelines

Observe the general safety regulation when handling chemicals

Other Regulations

OSHA: Hazardous by definition of Hazardous Communication Standard (29CFR 1910.1200)

WHMIS (Canada):

Class III Combustible liquid with a flash point of 38^{OC}

16. OTHER INFORMATION.

Date of Issue: 10 June 2016

Reason for Issue: Change to format, Rearrange sections

Replaces: Previous issue of 2016

Revision date: 01 May 2020

Abbreviations:

CAS No.	Chemical Abstract Number
ERMA	Environmental Risk Management Authority
HSNO	Hazardous Substances and New Organisms
NZCI	New Zealand Chemical Inventory
STEL	Short Term Exposure Limit
TWA	Time Weighted Average
WES	Workplace Exposure Standards

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.

PREPARED BY:

TECHNICAL SERVICES

