PO Box 14527, Wadeville 1422 562 Crocker Road Wadeville, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



TECHNICAL DATA SHEET Fleetline Brake Fluid Dot 4

PRODUCT DESCRIPTION

Brake fluid dot 4 is a high quality, high performance, high boiling point heavy duty dot 4 brake fluid for superior performance in conventional disk and drum brake systems in cars, trucks, buses and motorcycles.

PERFOMANCE STANDARDS

- SAE J1704
- FMVSS 116 DOT 4
- ISO 4925 Class4

BENEFITS

- It has low and high temperature viscosity behaviour to ensure good braking performance at all times.
- It has high boiling point to ensure good braking response even in high temperature and high load conditions.
- Its low temperature viscosity allows it to flow even during freezing conditions.
- It is compatible to both natural and synthetic rubber components in the brake system.
- Provides outstanding protection to brake system components from corrosion.

KEY PROPERTIES

Density @20°C kg/l	1.04
Viscosity @100°C (cSt)	1.5
Boiling point ^o C	260 min
Wet boiling point ^o C	155 min
FLASH POINT ⁰ C	90 min
Ignition temperature	300

PACKAGE SIZE	200 mL	500 mL	5 Litres	20 Litres	210 Litres
Fleetline Brake Fluid DOT 4	√	√	1	1	~



