

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET LUBE X 20W-50 SF/CD

PRODUCT DESCRIPTION

Lube X 20W-50 SF/CD is an entry spec, low tier engine oil designed for use in light delivery diesel engines and petrol engines. The oil contains a balanced additive package to prevent sludge formation and prevent corrosion and wear.

PERFORMANCE STANDARDS

- API SF CD
- MIL-L2104D
- MIL-L2164D
- DETROIT DIESEL
- FORD GM
- CCMC D2
- VOLVO VDS

APPLICATION

Lube X 20W-50 oil is intended for use in passenger cars, bakkies and light commercial vehicles in urban start-stop operations.

KEY PROPERTIES

SAE Grade	N/A	20W-50
Viscosity @40 °C	cSt	100
Viscosity @100 °C	cSt	12.7
Viscosity Index	N/A	110
Pour point	°C	-21

PACKAGE SIZE	500ml	4 Litres	5 Litres	20 Litres	210 Litres	1000 Litres
Lube X 20W-50	✓	✓	✓	✓	✓	✓

