PO Box 14527, Wadeville 1422 562 Crocker Road Wadeville, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



TECHNICAL DATA SHEET LUBE X EP 90 GL4

PRODUCT DESCRIPTION

LUBE X EP 90 GL-4 is a premium automotive gear oil formulated with special friction modifiers, virgin base oils, anti-wear, antioxidant, anti-foam, anti-corrosion and extreme pressure additives. This combination ensures smooth squeak and chatter free and good protection to the gear teeth.

PERFOMANCE STANDARDS

Viscosity grade SAE 90

Quality class API GL-4

BENEFITS

- EP 90 GL-4 is suitable for use in all manual gearboxes, which call for the API classification of GL-4.
- It resists scuffing and abrasive wear even under extremes of conditions.
- The additives used in the product help to prevent foaming and oxidation hence resulting in a long service life.

KEY PROPERTIES

Density @20 °C	kg/L	0.885
Viscosity @40 °C	cSt	180
Viscosity @100 °C	cSt	17
Viscosity Index	N/A	100

PACKAGE SIZE	500ml	5 Litres	20 Litres
LUBE X EP 90 GL4	1	1	1

