PO Box 14527, Wadeville 1422 562 Crocker Road Wadeville, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



MATERIAL SAFETY DATA SHEET EP 90 GL4

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: EP 90 GL4 **Manufacturer/Supplier** OILFLOW cc

562 Crocker Road, Wadeville, Germiston, South Africa

1422

Health Emergency Telephone 011 827 5848
Oilflow Website: www.oilflow.co.za

2. COMPOSITION/INFORMATION ON THE COMPONENTS

Hazardous Components in Product

Component Name Concentration R Phrases Classification

solvent refined mineral oil 98.00 Performance agents 2.00

3. HAZARD IDENTIFICATION

Main Hazards Not hazardous according to OSHA 29 CFR 1910.1200

Health Effects – Eyes May cause irritation to the eyes.

Health Effects – Skin No hazard providing normal cleansing is carried out.

Health Effects – Ingestion No problems expected for minor ingestion. However, for

amounts exceeding ½ litre give 1 or 2 glasses of water and

call a doctor.

Health Effects – Inhalation May cause irritation, dizziness or nausea if inhaled over a

prolonged period, especially whilst hot.

4. FIRST AID MEASURES

First Aid – Eyes Flush thoroughly with water. If irritation occurs, call a

doctor.

First Aid – Skin Wash skin with soap and water.

First Aid – Ingestion Wash out mouth with water. Obtain medical attention. Do

not induce vomiting.

First Aid – Inhalation Remove from exposure and if the patient experiences

irritation, nausea, or unconsciousness, seek medical

assistance.



PO Box 14527, Wadeville 1422 562 Crocker Road Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
F-mail: oilflow@oilflow

 $\hbox{E-mail: oilflow@oilflow.co.za}$

www.oilflow.co.za



MATERIAL SAFETY DATA SHEET EP 90 GL4

5. FIRE FIGHTING MEASURES

Extinguishing Media Use foam, dry chemical, carbon dioxide or water fog.

Unsuitable Extinguishing Media Do not use water jet. Special Hazards of Product No special hazards.

Protective Equip, for Fire-Fighting Wear self-contained breathing apparatus for fires in

enclosed spaces.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Material can create slippery conditions underfoot.

Environmental Precautions Try to prevent the material from entering drains or

watercourses. Spillages

Contain and absorb using diatomaceous earth or other inert material. Transfer into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling No special precautions are required.

Storage Storage temperature should be controlled to between 1 and

40°C. Where outside storage of drums is unavoidable, they should be stored horizontally to avoid ingress of water.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Standards

OIL MIST, CHEMICAL UK EH40: OES 5mg/m³ 8 h TWA. UK EH40: OES 10mg/m³ 15

min TWA.

Engineering Control Measures Exposure to this material may be controlled in several ways.

The measures appropriate for a worksite depend on how the material is used and on the potential for exposure. Use of the basic principles of industrial Hygiene will enable this

material to be used safely.

Respiratory Protection Respiratory protection is not normally required.

Hand Protection No special protection needed. However, good personal

hygiene practices should always be followed.

Eye Protection Chemical goggles if there is a risk of eye contact.

Body Protection Normal work wear.



PO Box 14527, Wadeville 1422 562 Crocker Road

Wadeville, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



MATERIAL SAFETY DATA SHEET EP 90 GL4

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Liquid Colour Amber Odour Faint рН N/A Boiling Range/Point (°C) > 320 Flash Point (PMCC) (°C) > 200 Solubility in Water (kg/m³) Insoluble Density (kg/m³) 0.885 Auto-flammability (°C) > 350 Viscosity (cSt) 180

10. STABILITY AND REACTIVITY

Stability Stable under normal conditions

Conditions to Avoid Strong oxidation

Materials to Avoid Strong oxidizing agents

Hazardous Decomposition Products Combustion will generate carbon monoxide and smoke,

possibly thick and choking, resulting in zero visibility.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity Low order of acute toxicity.

12. ECOLOGICAL INFORMATION

Mobility The product will leach into soil and will float on water. Persistence/Degradability

time.

The product is expected to biodegrade very slowly with

13. DISPOSAL

Product Disposal Dispose of in accordance with all applicable local and

national regulations.

Container Disposal An approved drum recycler can recycle containers.



PO Box 14527, Wadeville 1422 562 Crocker Road Wadeville, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



MATERIAL SAFETY DATA SHEET EP 90 GL4

14. TRANSPORT INFORMATION

Un Class Not classified IMO Class Not classified IMDG Class Not classified IATA Class Not classified

15. REGULATORY INFORMATION

Labelling information Irritant

Government Inventory Status Not established.

US Superfund Amendments This product contains no "Extremely Hazardous Substances"

16. OTHER INFORMATION

MSDS First Issued 01 May 2018 MSDS Data Revised 01 May 2020

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.

