
PO Box 14527, Wadeville 1422 562 Crocker Road Wadeville, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



TECHNICAL DATA SHEET Fleetline Antifreeze 50% Blue

PRODUCT DESCRIPTION

Antifreeze 50% blue is a pre-mixed Monoethyleneglycol based antifreeze and summer coolant containing a wide spectrum of corrosion inhibitors.

APPLICATION

Antifreeze 50% is for use in the cooling systems of motor vehicles and stationary engines, which use water as a coolant. Its high concentration of Monoethyleneglycol enables the product to protect to low temperatures at high levels of dilution. Its broad spectrum of corrosion inhibitors ensures that no corrosion takes place in iron or aluminum components, thus giving long life. For maximum protection, Antifreeze 50% is ready as is for use.

BENEFITS

- Effective protection against cold
- Protects against corrosions
- Prevents against foaming
- Keeps the cooling system clean

KEY PROPERTIES

Appearance Blue

Density @ 20°C kg/l 1.125

Freezing Point -40°C

PACKAGE SIZE	1 Litre	5 Litres	20 Litres	210 Litres
Antifreeze 50% Blue	1	1	\	✓

