

PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## TECHNICAL DATA SHEET

### Fleetline Antifreeze 50%

#### PRODUCT DESCRIPTION

Antifreeze 50% is a pre-mixed Monoethyleneglycol based antifreeze and summer coolant containing a wide spectrum of corrosion inhibitors.

#### APPLICATION

Antifreeze 50% is for use in the cooling systems of motor vehicles and stationary engines, which use water as a coolant. Its high concentration of Monoethyleneglycol enables the product to protect to low temperatures at high levels of dilution. Its broad spectrum of corrosion inhibitors ensures that no corrosion takes place in iron or aluminum components, thus giving long life. For maximum protection, Antifreeze 50% is ready as is for use.

#### BENEFITS

- Effective protection against cold
- Protects against corrosions
- Prevents against foaming
- Keeps the cooling system clean

#### KEY PROPERTIES

Appearance                      Fluorescent yellow

Density @ 20°C kg/l            1.125

Freezing Point                    -40°C

PACKAGE SIZE	1 Litre	5 Litres	20 Litres	210 Litres	1000 Litres
Antifreeze 50%	✓	✓	✓	✓	✓

