

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET

Fleetline EP 75W90 GL5 SYN

PRODUCT DESCRIPTION

Fleetline EP 75W-90 GL-5 full synthetic gear oil is designed to combat problems associated with gear selection and overheating in highly stressed powertrains. Formulated using a high level of Polyalphaolefin synthetic hydrocarbon technology and performance additives to provide outstanding lubrication at extreme operating temperatures where conventional oils begin to degrade. EP 75W-90 synthetic gear oil is recommended for use in both automotive gearboxes and hypoid axles where an SAE 75W-90 grade has been specified. It is also recommended for Ford high speed and other multi-speed gearboxes and can be used with confidence for topping-up wherever an SAE 80W-90 has been specified.

PERFORMANCE STANDARDS

- API GL-5
- Ford M2C-175A
- MIL 2105D
- MB235.8
- ZF TE ML 02B, 05B.

BENEFITS

- Excellent load stress capacity.
- Excellent anti-wear and extreme pressure performance.
- Excellent rust and corrosion protection.
- Fully compatible with conventional gear oils.
- Excellent thermal stability and resistance to oxidation.



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET

Fleetline EP 75W90 GL5 SYN

KEY PROPERTIES

Density @20 °C	Kg/L	0.875
Viscosity 40 °C	cSt	106
Viscosity 100 °C	cSt	17.2
Viscosity Index	N/A	175
Flash point	°C	220
Pour point	°C	-45

PACKAGE SIZE	500ml	5 Litres	20 Litres	210 Litres
EP 75W-90 GL5	✓	✓	✓	✓

