PO Box 14527, Wadeville 1422 562 Crocker Road Wadeville, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



TECHNICAL DATA SHEET Fleetline EP 80W90 GL4

PRODUCT DESCRIPTION

EP 80W-90 GL-4 is an automotive gear oil blended from virgin base oils, which have been fortified with antiwear, anti-oxidant, anti-foam, anti-corrosion and extreme pressure additives. It is suitable for use in heavily and medium loaded transmission in passenger cars, commercial vehicles, trucks, buses and other modes of transport.

PERFOMANCE STANDARDS

- API GL-4
- MIL-L-2105
- ZFTE-L08
- ZFTE- M08

BENEFITS

- Resists scuffing and abrasive wear even under extremes of conditions.
- It prevents foaming and oxidation hence resulting in a long service life.

KEY PROPERTIES

SAE GRADE		80W-90	
Density @20 °C	kg/L	0.895	
Viscosity @40 °C	cSt	160	
Viscosity @100 °C	cSt	15.2	
Viscosity Index		95	
Pour point	°C	-9	

PACKAGE SIZE	5 Litres	20 Litres	210 Litres
EP 80W-90 GL4	1	4	4

