

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline EP 85W140 GL5

PRODUCT DESCRIPTION

EP 85W-140 GL-5 is an automotive gear oil blended from virgin base oils which has been fortified with anti-wear, antioxidant, anti-foam, anti-corrosion and extreme pressure additives. It is suitable for use in final drives which require the API specification level of GL-5.

PERFORMANCE STANDARDS

- Viscosity grade SAE 85W-140
- Quality class API GL-5
- MIL-2105
- MB 235.6
- ZF-TE-ML 05A, 7A, 12E, 16B, C & D, 17B, 19B, 21A
- Volvo 1273.10

APPLICATIONS

- 85W-140 GL-5 is suitable for use in all final drives which call for the API classification of GL-5.
- It resists scuffing and abrasive wear even under extremes of conditions.
- It is also used for certain manual gear boxes where EP gear oil is recommended.

KEY PROPERTIES

Density @20 °C	kg/L	0.950
Viscosity @40 °C	cSt	350
Viscosity @100 °C	cSt	28
Viscosity Index		130
Pour point	°C	-15
Flash point C.O.C.	°C	200
Boiling point	°C	350

PACKAGE SIZE	500 mL	5 Litres	20 Litres	210 Litres
Fleetline EP 85W-140 GL5	✓	✓	✓	✓

