


PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Driveline SAE 40 Regen

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Driveline SAE 40 Regen
Manufacturer/Supplier: OILFLOW cc
562 Crocker Road, Wadeville, Germiston, South Africa
1422
Health Emergency Telephone: 011 827 5848
Oilflow Website: www.oilflow.co.za

2. COMPOSITION/INFORMATION ON THE COMPONENTS

Hazardous Components in Product

Component Name	Concentration
Solvent refined mineral oil	95-98
Performance agents	2- 5

3. HAZARD IDENTIFICATION

Main Hazards: Not hazardous according to OSHA 29 CFR 1910.1200
Health Effects – Eyes: May cause irritation to the eyes.
Health Effects – Skin: No hazard provided normal cleansing is carried out.
Health Effects – Ingestion: No problems expected for minor ingestion. However, for amounts exceeding ½ liter. Give 1 or 2 glasses of water and call the doctor
Health Effects Inhalation: May cause irritation, dizziness or nausea if inhaled over a prolonged period especially whilst hot.

4. FIRST AID MEASURES

First Aid – Eyes: Flush thoroughly with water. If irritation occurs, call a doctor.
First Aid – Skin: Wash skin with soap and water.
First Aid – Ingestion: Wash out mouth with water. Obtain medical attention. Do not induce vomiting.
First Aid – Inhalation: Remove from exposure and if the patient experiences irritation, nausea or unconsciousness seek medical help.


5. FIRE FIGHTING MEASURES

Extinguishing Media: Use foam, dry chemical, carbon dioxide or water fog.
Unsuitable Extinguishing Media: Do not use water jet.
Special Hazards of Product: No special hazards
Protective Equip. for Fire-Fighting spaces: Wear self-contained breathing apparatus for fires in enclosed spaces



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Driveline SAE 40 Regen

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions
Environmental Precautions
Spillages

Material can create slippery conditions underfoot.
Try to prevent the material from entering drains or watercourses.
Contain and absorb using diatomaceous earth or other inert materials. Transfer into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling
Storage

No special precautions are required.
Storage temperature should be controlled to between 1 and 40°C. Where outside storage of drums is unavoidable, they should be stored horizontally to avoid ingress of water.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Occupational Exposure Standards

OIL MIST, MINERAL

UK EH40: OES 5mg/m³ 8 h TWA. UK EH40: OES 10mg/m³ 15 min TWA.

Engineering Control Measures
The measures appropriate

Exposure to this material may be controlled in a number of ways.

Respiratory Protection
Hand Protection

For a particular worksite depend on how the material is used and on the potential for exposure. Use of the basic principles of Industrial Hygiene will enable this material to be used safely.

Eye Protection
Body Protection

Respiratory protection is not normally required.
No special protection needed. However, good personal hygiene practices should always be followed.
Chemical goggles if there is a risk of eye contact.
Normal work wear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State
Colour
Odour
pH
Boiling Range/Point (°C)
Flash Point (PMCC) (°C)
Solubility in Water (kg/m³)
Density (kg/m³)
Auto-flammability (°C)
Viscosity (cSt)

Liquid
Amber
Faint
N/A
Boils above 320
Exceeds 200
Insoluble
0.881 typ.
Above 350
100 typ.



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Driveline SAE 40 Regen

10. STABILITY AND REACTIVITY

Stability
Conditions to Avoid
Materials to Avoid
Hazardous Decomposition Products

Stable under normal conditions
Strong oxidation
Strong oxidizing agents
Combustion will generate carbon monoxide and smoke, possibly thick and choking, resulting in zero visibility.

11. TOXOLOGICAL INFORMATION

Acute Toxicity

Low order of acute toxicity

12. ECOLOGICAL INFORMATION

Mobility
Persistence/Degradability

The product will leach into soil and will float on water.
The product is expected to biodegrade very slowly with time

13. DISPOSAL

Product Disposal

Dispose of in accordance with all applicable local and national regulations.

Container Disposal

The product may also be burned in an enclosed burner.
An approved drum recycler can recycle containers.

14. TRANSPORT INFORMATION

UN Class
IMO Class
IMDG Class
IATA Class

Not classified
Not classified
Not classified
Not classified

15. REGULATORY INFORMATION

Labelling Information
Government Inventory Status
US Superfund Amendments

Irritant
Not established
This product contains no "Extremely Hazardous Substances"



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Driveline SAE 40 Regen

16. OTHER INFORMATION

MSDS First Issued
Product Use

01 November 2021
Automotive engine oil

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.

