

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline 10W30 SN CF Full Synthetic

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: Fleetline 10W30 SN CF Full Synthetic
Manufacturer/Supplier: OILFLOW cc
562 Crocker Road, Wadeville, Germiston, South Africa
1422
Health Emergency Telephone: 011 827 5848
Oilflow Website: www.oilflow.co.za

2. COMPOSITION/INFORMATION ON THE COMPONENTS

Hazardous Components in Product

Component Name	Concentration	R Phrases	Classification
Solvent refined mineral oil	75.00 – 90.00		
Performance agents	10 – 25.00		

3. HAZARD IDENTIFICATION

Main Hazards: Not hazardous according to OSHA 29 CFR 1910.1200

Health Effects – Eyes: May cause irritation to the eyes.

Health Effects – Skin: No hazard provided normal cleansing is carried out.

Health Effects – Ingestion: No problems expected for minor ingestion. However, for amounts exceeding ½ litre. Give 1 or 2 glasses of water and call the doctor

Health Effects Inhalation: May cause irritation, dizziness or nausea if inhaled over a prolonged period especially whilst hot.



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline 10W30 SN CF Full Synthetic

4. FIRST AID MEASURES

First Aid – Eyes

Flush thoroughly with water. If irritation occurs, call a doctor.

First Aid – Skin

Wash skin with soap and water.

First Aid – Ingestion

Wash out mouth with water. Obtain medical attention.
Do not induce vomiting.

First Aid – Inhalation

Remove from exposure and if the patient experiences irritation, nausea, or unconsciousness seek medical help.

5. FIRE FIGHTING MEASURES

Extinguishing Media

Use foam, dry chemical, carbon dioxide or water fog.

Unsuitable Extinguishing Media

Do not use water jet.

Special Hazards of Product

No special hazards

Protective Equip. for Fire-Fighting

Wear self-contained breathing apparatus for fires in enclosed spaces

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions

Material can create slippery conditions underfoot.

Environmental Precautions

Try to prevent the material from entering drains or watercourses.

Spillages

Contain and absorb using diatomaceous earth or other inert materials. Transfer into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling

No special precautions are required.

Storage

Storage temperature should be controlled to between 1 and °C. Where outside storage of drums is unavoidable, they



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline 10W30 SN CF Full Synthetic

should be
stored horizontally to avoid ingress of
water.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Occupational Exposure Standards

OIL MIST, MINERAL

UK EH40: OES 5mg/m³ 8 h TWA. UK EH40: OES 10mg/m³
15 min TWA.

Engineering Control Measures

Exposure to this material may be controlled in a number
of ways. The measures appropriate

For a worksite depend on how the material is
used and on the potential for exposure. Use of
the basic principles of Industrial Hygiene will
enable this material to be used safely.

Respiratory Protection

Respiratory protection is not normally required.

Hand Protection

No special protection needed. However, good personal
hygiene
practices should always be followed.

Eye Protection

Chemical goggles if there is a risk of eye contact.

Body Protection

Normal work wear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State

Liquid

Colour

Amber

Odour

Faint

pH

N/A

Boiling Range/Point (°C)

Boils above 320 °C

Flash Point (PMCC) (°C)

Exceeds 200 °C

Solubility in Water (kg/m³)

Insoluble



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline 10W30 SN CF Full Synthetic

Density (kg/m ³) @20°C	0.875
Auto-flammability (°C)	Above 350°C
Viscosity (cSt) @40°C	70 typ

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions
Conditions to Avoid	Strong oxidation
Materials to Avoid	Strong oxidizing agents
Hazardous Decomposition Products	Combustion will generate carbon monoxide and smoke, possibly thick and choking, resulting in zero visibility.

11. TOXOLOGICAL INFORMATION

Acute Toxicity	Low order of acute toxicity
----------------	-----------------------------

12. ECOLOGICAL INFORMATION

Mobility	The product will leach into soil and will float on water.
Persistence/Degradability	The product is expected to biodegrade very slowly with time

13. DISPOSAL

Product Disposal	Dispose of in accordance with all applicable local and national regulations. The product may also be burned in an enclosed burner.
Container Disposal	An approved drum recycler can recycle containers.

14. TRANSPORT INFORMATION

UN Class	Not classified
IMO Class	Not classified
IMDG Class	Not classified
IATA Class	Not classified



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline 10W30 SN CF Full Synthetic

15. REGULATORY INFORMATION

Labelling Information
Government Inventory Status
US Superfund Amendments

Irritant
Not established
This product contains no "Extremely Hazardous Substances"

16. OTHER INFORMATION

MSDS First Issued 09 My 2023
MSDS Data Revised
Product Use Automotive engine oil

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.

