PO Box 14527, Wadeville 1422 562 Crocker Road Wadeville, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



MATERIAL SAFETY DATA SHEET Fleetline SAE 30 SF CF

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: FLLEETLINE SAE 30 SF CF4

Manufacturer/Supplier OILFLOW cc

562 Crocker Road, Wadeville, Germiston, South Africa

1422

Emergency Telephone 011 827 5848
Website: www.oilflow.co.za

2. COMPOSITION/INFORMATION ON THE COMPONENTS

Hazardous Components in Product

Component Name Concentration R Phrases Classification

Solvent refined mineral oil 94.00 – 97.00 Asp. Tox. H304 May lead to congestion of airways Performance agents 3.00 - 6.00 Xn Harmful if swallowed

3. HAZARD IDENTIFICATION

Main Hazards Not hazardous according to OSHA 29 CFR 1910.1200

Health Effects – EyesMay cause irritation to the eyes.

Health Effects – SkinNo hazard provided normal cleansing is carried out.

Health Effects – IngestionNo problems expected for minor ingestion. However, for amounts

exceeding $\frac{1}{2}$ litre give

1 or 2 glasses of water and call a doctor.

Health Effects - Inhalation May cause irritation, dizziness or nausea if inhaled over a prolonged period,

especially whilst hot.

4. FIRST AID MEASURES

First Aid – Eyes Flush thoroughly with water. If irritation occurs, call a doctor.

First Aid – Skin Wash skin with soap and water.

First Aid – Ingestion Wash out mouth with water. Obtain medical attention. Do not induce

vomiting.

First Aid – Inhalation Remove from exposure and if the patient experiences irritation, nausea or

unconsciousness seek medical assistance.

5. FIRE FIGHTING MEASURES

Unsuitable Extinguishing Media Do not use water jet. Special Hazards of Product No special hazards

Protective Equip. for Fire-Fighting Wear self-contained breathing apparatus for fires in enclosed spaces.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Material can create slippery conditions underfoot.

Environmental Precautions

Try to prevent the material from entering drains or watercourses.

Spillages

Contain and absorb using diatomaceous earth or other inert materials.

Transfer into suitable containers for disposal





PO Box 14527, Wadeville 1422 562 Crocker Road Wadeville, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



MATERIAL SAFETY DATA SHEET Fleetline SAE 30 SF CF

7. HANDLING AND STORAGE

Handling No special precautions are required.

Storage temperature should be controlled to between 1 and 40°C. Where Storage

outside storage drums is unavoidable, they should be stored horizontally to

avoid ingress of water.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Standards

OIL MIST, MINERAL UK EH40: OES 5mg/m³ 8 h TWA. UK EH40: OES 10mg/m³ 15 min TWA.

Engineering Control Measures Exposure to this material may be controlled in a number of ways. The

measures appropriate

For a particular worksite depend on how the material is used and on the

potential for exposure.

Use of the basic principles of Industrial Hygiene will enable this material to

be used safely.

Respiratory Protection Respiratory protection is not normally required.

No special protection needed. However, good personal hygiene practices **Hand Protection**

should always be followed

Eve Protection Chemical goggles if there is a risk of eye contact.

Body Protection Normal work wear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State Liquid Colour Brown

Odour Petroleum odour

pН N/A Boiling Range/Point (°C) No data Flash Point (PMCC) (°C) Exceeds 180 Solubility in Water (kg/m³) Insoluble Density (kg/m³) @20°C 0.881 Auto-flammability (°C) Above 350 90

Viscosity (cSt) @40°C

10. STABILITY AND REACTIVITY

Stable under normal conditions Stability

Conditions to Avoid Strong oxidation **Materials to Avoid** Strong oxidizing agents

Hazardous Decomposition Products Combustion will generate carbon monoxide and smoke, possibly thick and

choking resulting in zero visibility.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity Low order of acute toxicity

12. ECOLOGICAL INFORMATION

Mobility The product will leach into soil and will float on water.



PO Box 14527, Wadeville 1422 562 Crocker Road Wadeville, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



MATERIAL SAFETY DATA SHEET Fleetline SAE 30 SF CF

Persistence/Degradability The product is expected to biodegrade very slowly with time.

13. DISPOSAL

Product Disposal Dispose of in accordance with all applicable local and national regulations.

The product may also be burned in an enclosed burner.

Container Disposal An approved drum recycler can recycle containers.

14. TRANSPORT INFORMATION

UN Class
IMO Class
IMO Class
IMDG Class
INot classified
IMTA Class
Not classified
Not classified

15. REGULATORY INFORMATION

Labelling Information Irritant

Government Inventory Status Not established

US Superfund Amendments This product contains no "Extremely Hazardous Substances"

16. OTHER INFORMATION

MSDS Issue24 June 2018MSDS Revision01 May 2020Product UseAutomotive engine oil

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.

