

PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: [oilflow@oilflow.co.za](mailto:oilflow@oilflow.co.za)  
[www.oilflow.co.za](http://www.oilflow.co.za)



## TECHNICAL DATA SHEET FLEETLINE 15W40 CH4 SJ

---

### PRODUCT DESCRIPTION

ALLFLEET 15W-40 CH4 SJ is a mineral engine oil incorporating a special blend of base stocks and versatile additive package which provides maximum engine power and protection. It is designed for lubrication of the most diesel engines with turbocharging and injection pumps. It meets or exceeds the requirements of CH4/SJ or lesser specification engine oil. It provides a high level of protection against wear, sludge deposit and acid attack.

### PERFORMANCE STANDARDS

- API CH4 SJ,
- ACEA A3/B3
- MB 228.3, 229.1
- MAN 3275,
- VOLVO VDS
- MUT Type 2,
- DEUTZ II
- MACK EO-M plus,
- Caterpillar ECF- 1a,
- Cummins
- CES 20076
- Renault RD

### BENEFITS

- Easier cold starting of the engine
- Excellent deposit control
- Keeps engine components clean and extends drain intervals
- Maximum engine performance



PO Box 14527, Wadeville 1422  
 562 Crocker Road  
 Wadeville, Johannesburg

Tel: (011) 827-5848  
 Fax: (011) 827-5832  
 E-mail: oilflow@oilflow.co.za  
 www.oilflow.co.za



## TECHNICAL DATA SHEET FLEETLINE 15W40 CH4 SJ

### APPLICATIONS

ALLFLEET 15W-40 SJ CH-4 oils are recommended for naturally aspirated and turbo charged diesel engines calling for API classification CH4 and SJ. They can also be used in a variety of other industrial applications, such as certain types of generators and off-road equipment's and machines requiring the use of an engine oil.

### KEY PROPERTIES

SAE Grade		15W-40
Density @20 °C	kg/L	0.886
Viscosity @40 °C	cSt	110
Viscosity @100 °C	cSt	14.2
Viscosity Index	N/A	130
Pour point	°C	-27
TBN	mg KOH/g	10min

PACKAGE SIZE	500 mL	5 Litres	20 Litres	210 Litres	1000 Litres
15W-40 ALLFLEET	✓	✓	✓	✓	✓

