

PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## TECHNICAL DATA SHEET

### Fleetline 15W-40 CI4 SL SUPER FLEET

---

#### PRODUCT DESCRIPTION

SUPERFLEET 15W-40 SL/CI4 is a high-performance diesel engine oil (HPDO) designed for the adverse and robust conditions. It can be used in systems having the exhaust gas recirculation or catalytic converter and is designed for powerful vehicles working in cycles of big individual mileage. It is capable of controlling wear on all critical engine parts.

#### PERFORMANCE STANDARDS

- API CI4/SL
- ACEA E7
- MB 228.3
- VOLVO VDS
- MAN M3275
- MTU type 2
- MACK EO-N
- RENAULT TRUCKS RLD-2
- CUMMINS CES 20076/77/78
- JASO DH-1
- DEUTZ DQC III
- CATERPILLAR ECF-2, ECF-1a
- Detroit Diesel DDC
- ALLISON C4 LEVEL
- Global DHD-1

#### APPLICATIONS

SUPERFLEET 15W-40 CI4/SL is designed for heavily loaded diesel engine trucks operating in robust conditions, earthmoving equipment, stationary engines cars and light commercials where a CI-4 Diesel rating or an SL petrol rating is required. It is also suitable for LPG fueled engines



PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## TECHNICAL DATA SHEET

### Fleetline 15W-40 CI4 SL SUPER FLEET

#### BENEFITS

- Guarantees easy start up even at low temperatures.
- Excellent soot control.
- Extended drain intervals.
- Maximum engine performance.
- Complies with the EURO 2 and EURO 3 technologies.

#### KEY PROPERTIES

SAE GRADE		15W-40
Density @20 °C	kg/L	0.887
Viscosity @40 °C	cSt	115
Viscosity @100 °C	cSt	14.6
Viscosity Index	N/A	130
Pour point	°C	-30
TBN	mg KOH/g	12
Flash point C.O.C.	°C	220
Colour	N/A	Amber

PACKAGE SIZE	4 Litres	5 Litres	20 Litres	210 Litres	1000 Litres
SUPERFLEET	✓	✓	✓	✓	✓

