PO Box 14527, Wadeville 1422 562 Crocker Road Wadeville, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



TECHNICAL DATA SHEET FLEETLINE 15W40 SF CF4

PRODUCT DESCRIPTION

Fleetline Turbomax 15W-40 SF/CF-4 is a high-quality multi-grade mineral engine oil designed for gasoline and diesel engines with or without turbochargers. The latest manufacturing technology and a special additive package provide optimum lubricating properties, engine cleanliness and maximum wear protection. It is specially designed for powerful engines operating in urban driving condition.

BENEFITS

- API CF4/SF
- ACEA E2-96,
- MB 228.0,
- MB 228.1,
- MAN 270,
- MAN 271.

BENEFITS

- Provides optimum lubricating properties
- Good deposit control
- Extended drain intervals
- Maximum engine performance

APPLICATIONS

• Fleetline Turbomax 15W-40 SF/CF-4 oils are designed especially for engines in passenger cars commercial vehicles and engines exposed to high shear stress in stop/start urban driving conditions.



PO Box 14527, Wadeville 1422 562 Crocker Road Wadeville, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



TECHNICAL DATA SHEET FLEETLINE 15W40 SF CF4

KEY PROPERTIES

Sae Grade		15W-40
Density @20 °C	kg/L	0.881
Viscosity @40 °C	cSt	105
Viscosity @100 °C	cSt	13.8
Viscosity Index		125
Pour point	°C	-24
TBN	mg KOH/g	10

PACKAGE SIZE	500ml	5 Litres	20 Litres	210 Litres
Turbomax 15W40	1	1	4	4

