

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET

Fleetline 20W50 SF CF

PRODUCT DESCRIPTION

FLEETLINE 20W-50 SF CF is a high performance multigrade diesel and petrol engine oil with a low phosphorus and low sulphated ash content designed for mixed fleet operators including those with petrol engines with catalytic converters.

PERFORMANCE STANDARDS

- API SF CF
- ACEA E5-2002
- MB 228.3
- VOLVO VDS 2
- MACK EOM PLUS
- MAN 3275
- MACK EO K/2

APPLICATIONS

Multigrade 20W-50 oils are recommended for naturally aspirated and turbo charged diesel engines and petrol engines calling for API CF/SF classification. They can also be used in passenger cars, commercial trucks and mini-buses or taxis.

KEY PROPERTIES

SAE GRADE	20W-50
Viscosity @40°C	175
Viscosity @100°C	17
Viscosity index	125
Pour Point	-24
TBN	8

PACKAGE SIZE	20 Litres	210 Litres
20W-50 SF CF	✓	✓

