

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET

Fleetline SAE 30 SF CF

PRODUCT DESCRIPTION

SAE 30 blended from virgin base oils which have been fortified with performance additives to meet the API SF/CF specification. It exhibits good resistance to oxidation, preventing the formation of deposits and varnishes.

PERFORMANCE STANDARDS

- API SF/CF
- MIL-L-2104C
- CCMC
- ALLISON C3
- VOLVO VDS
- MB 227
- MB 228

APPLICATIONS

- Premium monograde SF/CF oils are recommended for naturally aspirated and mildly turbo charged diesel and petrol engines calling for API classification SF & CF.
- It can be used in a variety application such as in passenger cars, light delivery vehicles, stationary engines and in farming machinery.

KEY PROPERTIES

SAE grade		30
Density 20 °C	kg/L	0.881
Viscosity 40 °C	cSt	92
Viscosity 100 °C	cSt	11
Viscosity Index	N/A	105
Pour point	°C	-21

PACKAGE SIZE	5 Litres	20 Litres	210 Litres
SAE 30 SF CF	✓	✓	✓

