

PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## TECHNICAL DATA SHEET

### Fleetline SAE 50 SF CF

#### PRODUCT DESCRIPTION

SAE 50 is premium monograde SF/CF engine oil blended from virgin base oils, which have been fortified with performance additives to meet the API SF/CF specification.

#### PERFORMANCE STANDARDS

API SF/CF  
MIL-L-2104C  
CCMC  
ALLISON C3  
VOLVO VDS  
MB 227  
MB 228

#### APPLICATIONS

Premium monograde SF/CF oil is recommended for naturally aspirated and mildly turbo charged diesel engines and petrol engines calling for API classification SF CF. They can be used in a variety of applications such as in passenger cars, light delivery vehicles and in farming machinery.

#### KEY PROPERTIES

SAE GRADE		50
Viscosity 40 °C	cSt	195
Viscosity 100 °C	cSt	18
Viscosity Index	N/A	100
Pour point	°C	-12
TBN	mg KOH/g	10.5

PACKAGE SIZE	20 Litres	210 Litres
SAE 50 SF CF	✓	✓

