

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET

Fleetline XTC 15W40 CI4

PRODUCT DESCRIPTION

Fleetline XTC 15W-40 CI4 is a premium high-performance heavy-duty semi synthetic diesel engine oil formulated with selected virgin base stocks and versatile additive package to provide maximum protection against wear, oxidation, deposit formation. The oil provides excellent equipment durability even under harsh, robust extreme operating conditions.

PERFORMANCE STANDARDS

- API CI4
- ACEA E7-16
- MB 228.3
- MAN 3275
- VOLVO VDS3
- MUT Type 2, DEUTZ III
- CUMMINS CES 20077,78
- Deutz DQC II
- Mack EO-N
- Mack EO- M+
- JASO DH-1
- Global DHD
- DDC 93K215

BENEFITS

- Easy cold starting of the engine.
- Superior protection from engine wear.
- Maintains engine power.
- Extended drain intervals in harsh conditions.
- Better fuel economy.



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET

Fleetline XTC 15W40 CI4

KEY PROPERTIES

Density @20 °C	kg/L	0.878
Viscosity @40 °C	cSt	108
Viscosity @100 °C	cSt	14
Viscosity Index		135
Pour point	°C	-30
Flash point C.O.C.	°C	220
TBN	mg KOH/g	11

PACKAGE SIZE	5 Litres	20 Litres	210 Litres
XTC 15W40 CI4	✓	✓	✓

