

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline Two Stroke Synthetic Oil

1. PRODUCT AND COMPANY IDENTIFICATION

Trade Name	FLEETLINE TWO STROKE OIL
Manufacturer/Supplier	OILFLOW LUBRICANTS 562 CROCKER RD WADEVILLE
Phone Number	(011) 827 5848
Fax Number	(011) 827 5832

2. COMPOSITION/INFORMATION ON THE COMPONENTS

Hazardous Components in Product

Component Name	Codes	Concentration	R Phrases	Classification
SYNTHETIC BASE OIL		76		
PERFORMANCE AGENTS		24.00		

3. HAZARD IDENTIFICATION

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

Adverse physicochemical, human health and environmental effects

No additional information available

Other hazards not contributing to the classification

This product floats on water and may affect the oxygen-balance in the water. The base oil contains less than 3% DMSO-extract measured according IP 346, therefore it is NOT classified as T/R45: May cause cancer" (Note L)."



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline Two Stroke Synthetic Oil

4. FIRST AID MEASURES

Symptoms/injuries after inhalation:	At normal temperatures, this product will be unlikely an Inhalation hazard.
Symptoms/injuries after skin contact	Unlikely to cause harm to the skin on brief or occasional but prolonged or repeated exposure may lead to dermatitis.
Symptoms/injuries after eye contact	unlikely to cause more than transient stinging or redness if accidentally eye contact occurs
Symptoms/injuries after ingestion	Bad taste unlikely to cause harm if accidentally swallowed in small doses though large quantities may cause nausea and diarrhoea

5. FIRE FIGHTING MEASURES

Extinguishing Media	Use foam, dry chemical dioxide, foam or water fog. Unsuitable Extinguishing Media Do not use water jet.
Special Hazards of Product	No special hazards.
Protective Equip, for Fire-Fighting	Wear self-contained breathing apparatus for fires in enclosed spaces.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Material can create slippery conditions underfoot.
Environmental Precautions watercourses.	Try to prevent the material from entering drains or
Spillages	Contain and absorb using diatomaceous earth or other inert material. Transfer into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling	No special precautions are required.
Storage	Storage temperature should be controlled to between 1 and 40°C. Where outside storage of drums is unavoidable, they should be stored horizontally to avoid ingress of water.


8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Standards OIL MIST, CHEMICAL	UK EH40: OES 5mg/m ³ 8 h TWA. UK EH40: OES 10mg/m ³ 15 min TWA.
---	---



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline Two Stroke Synthetic Oil

Engineering Control Measures

Exposure to this material may be controlled in several ways. The measures appropriate for a worksite depend on how the material is used and on the potential for exposure. Use of the basic principles of industrial Hygiene will enable this material to be used safely.

Respiratory Protection

Respiratory protection is not normally required.

Hand Protection

No special protection needed. However, good personal hygiene practices should always be followed.

Eye Protection

Chemical goggles if there is a risk of eye contact.

Body Protection

Normal work wear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Colour	Blue
Odour	Faint
pH	N/A
Flash Point (PMCC) (°C)	Exceeds 100 °C
Solubility in Water (kg/m ³)	Insoluble
Density (kg/m ³)	0.865 kg per litre
Auto-flammability (°C)	Above 200°C
Viscosity (cSt) @100	8
Viscosity (cSt) @40	40

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions
Conditions to Avoid	Extreme heat
Materials to Avoid	Strong oxidizing agents, strong acids
Hazardous Decomposition Products	CO ₂ , CO, PO _x , SO _x , H ₂ S and metal oxides

11. TOXICOLOGICAL INFORMATION

Acute Toxicity	Low order of acute toxicity.
----------------	------------------------------

12. ECOLOGICAL INFORMATION

Mobility	The product will leach into soil and will float on water and
----------	--



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline Two Stroke Synthetic Oil

Persistence/Degradability May affect the oxygen balance in water.
The product is expected to biodegrade very slowly with time.

13. DISPOSAL

Product Disposal Dispose of in accordance with all applicable local and national regulations.
Container Disposal An approved drum recycler can recycle containers.

14. TRANSPORT INFORMATION

Un Class Not classified
IMO Class Not classified
IMDG Class Not classified
IATA Class Not classified

15. REGULATORY INFORMATION

Labelling information Irritant
Government Inventory Status Not established.
US Superfund Amendments This product contains no "Extremely Hazardous Substances"

16. OTHER INFORMATION

MSDS First Issued 01 May 2018
MSDS Data Revised 01 May 2020
Product Use Two stroke oil

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.

