

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET

Fleetline Outboard TC-W3

PRODUCT DESCRIPTION

Fleetline Outboard TC-W3 is a high non-ash forming, detergent and dispersant two stroke outboard motor oil. The blend meets and exceeds the performance requirements of NMMA TC-W3. It contains specialised additives such as anti-wear, antioxidant, anti-rust, anti-corrosion, and other additives designed to control deposits and ring sticking and avoid plug fouling and pre-ignition. Oilflow Outboard TC-W is an SAE 40 oil, and with the addition of a diluent, thinned to be ready mix for use.

PERFORMANCE LEVEL AND SPECIFICATIONS

NMMA (National Marine Manufacturers Association) TC-W III.

APPLICATION

- Outboard TC-W3 is recommended for use in all high output, water cooled two stroke engines including Archimedes-Penta, British Anzani, Carniti, Chrysler, Crescent, Evinrude, Johnson, Mariner, Mercury, Penta, Seagull, Tohatsu, West Bend and Yamaha.
- Fleetline Outboard may be used either as a premix in engine fuel, or in a separate tank supplying a positive injection system.

BENEFITS

- Prevents ring sticking, smooth engine performance.
- excellent lubrication protection at all speeds and loads.
- No plug fouling and longer plug life.
- Minimum deposits, thus keeping rings free.



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848

Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



TECHNICAL DATA SHEET

Fleetline Outboard TC-W3

KEY PROPERTIES

SAE	N/A	40
Density @15 °C	kg/L	0.854
Viscosity @40 °C	cSt	40
Viscosity @100 °C	cSt	6.5
Viscosity Index	N/A	125
Pour point	°C	-33
Flash point C.O.C.	°C	80 max
Sulphated Ash % m/m	N/A	Nil

PACKAGE SIZE	500 mL	1 Litre	5 Litres	20 Litres
Fleetline Outboard TC-W3	✓	✓	✓	✓

