

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET

Fleetline Two Stroke Synthetic

PRODUCT DESCRIPTION

Fleetline Synthetic Two stroke oil incorporates a special additive package and polymers to produce this synthetic low-ash multifunctional for air cooled two-stroke engine oils. The oil meets the performance requirements including JASO FC, API-TC+, ISO EGC & EGD and Thailand Industrial Standards Institute (T.I.S.I. 1040). The oil is suitable for lubricating two stroke motors such as lawn mowers, scooters, motorcycles and chain saws.

BENEFITS

- Strong detergent performance.
- No smoke operation.
- Prevents plug fouling and piston crown deposit.
- Prevents ring sticking.
- Protect against rust, wear, and corrosion.
- Lubricates at even high speeds and loads.

APPLICATIONS

Always refer to the equipment manufacturers manual to check the recommended oil/fuel ratio, but as a general guide 1:20 oil /fuel ratio is suitable.

KEY PROPERTIES

SAE		20
Density 20 °C	kg/L	0.855
Viscosity 40 °C	cSt	40
Pour point	°C	-75
Flash point C.O.C.	°C	75
Colour	N/A	Blue



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET

Fleetline Two Stroke Synthetic

PACKAGE SIZE	500ml	1Litre	5 Litres	20 Litres	210 Litres	1000 Litres
Two Stroke Synthetic	✓	✓	✓	✓	✓	✓

