

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET

Fleetline UTTO 80W

PRODUCT DESCRIPTION

Fleetline UTTO 80W is a premium off-road technology multifunctional oil specifically blended for gear axles and hydraulic systems for heavy duty vehicles and agricultural equipment and machinery with or without wet brakes and limited slip differentials.

APPLICATION

- Fleetline UTTO 80W is suitable for applications calling for UTTO / THF oils, providing the final drive, hydraulic, wet brake, clutch and transmission performance needed in today's tractors.
- The oil is particularly useful in imparting friction stability to tractor oils. Friction stability is a key solution to robust wet-brake pump and transmission performance.

BENEFITS

- Excellent protection to gears, axles and hydraulic systems.
- Reduces noises encountered in wet brakes.
- Superior load carrying and wear protection.
- Oxidation and deposits control for improved cleanliness.

KEY PROPERTIES

SAE GRADE		80W
Density @20 °C	kg/L	0.870
Viscosity @40 °C	cSt	65
Viscosity @100 °C	cSt	10.8
Viscosity Index		155
Pour point	°C	-20
Flash point C.O.C.	°C	210
Colour	N/A	Amber

PACKAGE SIZE	20 Litres	210 Litres
UTTO 80W	✓	✓

