PO Box 14527, Wadeville 1422 562 Crocker Road Wadeville, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



TECHNICAL DATA SHEET Fleetline Lithium Graphite Grease

PRODUCT DESCRIPTION

Lithium Graphite Grease EP 2 is a Blackish / Dark Grey color grease containing premium quality base oils, calcium base soap and finely dispersed lubricating graphite.

APPLICATION

Fleetline Lithium Graphite Grease EP 2 is recommended for use in open gears, pantographs, pump glands, link pins, bushes and linkages. It could be used in rail and flange lubricating equipment, pantograph copper strips, contact wires, steam locomotive pins, bogie centres, synchro-lift wire ropes and it is ideally suited for plain bearings on welding machines or where plain bearings are badly worn.

BENEFITS

- Lowers maintenance costs: Fleetline Lithium Graphite Grease EP 2 lubricant protects against component wear under high load conditions and shock loading
- **Ease of application**: Good pump ability characteristics of calcium thickener provide suitable flow properties for grease pump application systems.
- Reduces re-lubrication costs: Superior adhesiveness ensures grease stays in placed and resist leakage, as well as in typical severity and shock load conditions.

KEY PROPERTIES

Thickening agent	Graphite
Colour	Grey/ Black
NLGI Classification	2
Penetration	280
Drop point °C	90
Graphite Content	10



PO Box 14527, Wadeville 1422 562 Crocker Road Wadeville, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832

E-mail: oilflow@oilflow.co.za

www.oilflow.co.za



TECHNICAL DATA SHEET Fleetline Lithium Graphite Grease

PACKAGE SIZE	15kg
Lithium Graphite Grease	1

