

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline Compressor 32

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: FLEETLINE COMPRESSOR 32
Manufacturer/Supplier: OILFLOW cc
P.O. Box 14527
562 Crocker Road, Wadeville, Germiston, South Africa
1422
Health Emergency Telephone: 011 827 5848
Oilflow Website: www.oilflow.co.za

2. COMPOSITION/INFORMATION ON THE COMPONENTS

Hazardous Components in Product

Component Name	Concentration	R Phrases	Classification
SOLVENT REFINED MINERAL OIL	>98.00		
PERFORMANCE AGENTS	<2.00		

3. HAZARD IDENTIFICATION

Main Hazards Not hazardous according to OSHA 29 CFR 1910.1200
Health Effects – Eyes May cause irritation to the eyes.
Health Effects – Skin No hazard providing normal cleansing is carried out.
Health Effects – Ingestion No problems expected for minor ingestion. However, for amounts exceeding ½ litre give 1 or 2 glasses of water and call a doctor.
Health Effects – Inhalation May cause irritation, dizziness or nausea if inhaled over a prolonged period, especially whilst hot.

4. FIRST AID MEASURES

First Aid – Eyes Flush thoroughly with water. If irritation occurs, call a doctor.
First Aid – Skin Wash skin with soap and water.
First Aid – Ingestion Wash out mouth with water. Obtain medical attention. Do not induce vomiting.
First Aid – Inhalation Remove from exposure and if the patient experiences irritation, nausea or unconsciousness, seek medical assistance.

5. FIRE FIGHTING MEASURES



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline Compressor 32

Extinguishing Media
Unsuitable Extinguishing Media
Special Hazards of Product
Protective Equip, for Fire-Fighting

Use foam, dry chemical, carbon dioxide or water fog.
Do not use water jet.
No special hazards.
Wear self-contained breathing apparatus for fires in enclosed spaces.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions
Environmental Precautions
Spillages

Material can create slippery conditions underfoot.
Try to prevent the material from entering drains or watercourses.
Contain and absorb using diatomaceous earth or other inert material. Transfer into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling
Storage

No special precautions are required.
Storage temperature should be controlled to between 1 and 40°C.
Where outside storage of drums is unavoidable, they should be stored horizontally to avoid ingress of water.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Standards
OIL MIST, CHEMICAL

UK EH40: OES 5mg/m³ 8 h TWA. UK EH40: OES 10mg/m³ 15 min TWA.

Engineering Control Measures

Exposure to this material may be controlled in several ways. The measures appropriate for a worksite depend on how the material is used and on the potential for exposure. Use of the basic principles of industrial Hygiene will enable this material to be used safely.

Respiratory Protection
Hand Protection

Respiratory protection is not normally required.
No special protection needed. However, good personal hygiene practices should always be followed.

Eye Protection
Body Protection

Chemical goggles if there is a risk of eye contact.
Normal work wear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State
Colour
Odour

Liquid
Amber
Faint



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline Compressor 32

pH	N/A
Boiling Range/Point (°C)	>320
Flash Point (PMCC) (°C)	>200
Solubility in Water (kg/m ³)	Insoluble
Density @ 20 °C (kg/m ³)	0.865
Auto-flammability (°C)	>350
Viscosity @40 °C (cSt)	32

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions
Conditions to Avoid	Strong oxidation
Materials to Avoid	Strong oxidizing agents
Hazardous Decomposition Products	Combustion will generate carbon monoxide and smoke, possibly thick and choking, resulting in zero visibility.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity	Low order of acute toxicity.
----------------	------------------------------

12. ECOLOGICAL INFORMATION

Mobility	The product will leach into soil and will float on water.
Persistence/Degradability	The product is expected to biodegrade very slowly with time.

13. DISPOSAL

Product Disposal	Dispose of in accordance with all applicable local and national regulations.
Container Disposal	An approved drum recycler can recycle containers.

14. TRANSPORT INFORMATION

Un Class	Not classified
IMO Class	Not classified
IMDG Class	Not classified
IATA Class	Not classified

15. REGULATORY INFORMATION

Labelling information	Irritant
-----------------------	----------



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline Compressor 32

Government Inventory Status
US Superfund Amendments

Not established.
This product contains no "Extremely Hazardous Substances"

16. OTHER INFORMATION

MSDS First Issued	01 May 2001
MSDS Data Revised	01 May 2020
Product Use	Compressor Oil.

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.

PREPARED BY: TECHNICAL SERVICES

