Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



MATERIAL SAFETY DATA SHEET FLEETLINE CIRCULATING (32,46,68,100,150,220)

1. PRODUCT AND COMPANY IDENTIFICATION

Trade Name Manufacturer/Supplier FLEETLINE CIRCULATING OILS OILFLOW cc P.O.Box 14527 4 Saligna Road, Boksburg, South Africa

Phone Number
Fax Number
Oilflow Website:

1422 (011) 827-5848 (011) 827-5832 www.oilflow.co.za

2. COMPOSITION/INFORMATION ON THE COMPONENTS Hazardous Components in Product

Component Name	Concentration
SOLVENT REFINED MINERAL	99.15
Additives package	0.85

3. HAZARD IDENTIFICATION

If skin contact occurs wash exposed areas with soap and water launder contaminated clothing.

Main Hazards	Not hazardous according to OSHA 29 CFR 1910.1200
Health Effects – Eyes	Not expected to cause eye irritation.
Health Effects – Skin	Expect to cause no more than minor skin irritation.
	Prolong or Frequently repeated contact may cause
	more severe irritation or may cause the skin to
	become racked or dry from defatting action of the material.
Health Effects – Inhalation	May cause irritation, dizziness or nausea if inhaled over a prolonged period, especially whilst hot
Health Effects - Oral	If more than several mouthfuls are swallowed, abdominal discomfort, nausea, and diarrhoea my occur.

4. FIRST AID MEASURES

First Aid – Eyes	Flush thoroughly with water.
	If irritation occurs, call a doctor.
First Aid – Skin	Wash skin with soap and water.
First Aid – Ingestion	If swallowed and person is conscious, give water or milk. Do not
	make person vomit except on advice of medical personnel. If



Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



MATERIAL SAFETY DATA SHEET FLEETLINE CIRCULATING (32,46,68,100,150,220)

advice cannot be obtained, take person and ontainer (or label) to nearest emergency treatment centre, never give anything by mouth to unconscious person.

First Aid – Inhalation

Remove from exposure and if the patient experiences irritation, nausea or unconsciousness, seek medical assistance.

5. FIRE FIGHTING MEASURES

Extinguishing Media Use foam, dry chemical, carbon dioxide or water fog. Unsuitable Extinguishing Media Do not use water jet. Special Hazards of Product No special hazards. Wear self-contained breathing apparatus for fires in enclosed Protective Equip, for Fire-Fighting spaces. Igniting temperature N/A Flammable limits N/A Flash Point 210 - 240°C Long term toxic the base oil components are not expected to be carcinogenic based on IARC criteria. This product has not been tested for

chronic health effects.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Material can create slippery conditions underfoot.
Environmental Precautions	Try to prevent the material from entering drains or
	watercourses.
Spillages	Contain and absorb using diatomaceous earth or other inert material. Transfer into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling	No special precautions are required.
Storage	Storage temperature should be controlled to between 1 and 40°C.
	Where outside storage of drums is unavoidable, they should be
	stored horizontally to avoid ingress of water.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Standards



Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



MATERIAL SAFETY DATA SHEET FLEETLINE CIRCULATING (32,46,68,100,150,220)

OIL MIST, CHEMICAL	UK EH40: OES 5mg/m ³ 8 h TWA. UK EH40: OES 10mg/m ³ 15 min TWA.
Engineering Control Measures	Exposure to this material may be controlled in several ways. The measures appropriate for a worksite depend on how the material is used and on the potential for exposure. Use of the basic principles of industrial Hygiene will enable this material to be used safely.
Respiratory Protection	Respiratory protection is not normally required.
Hand Protection	No special protection needed. However, good personal hygiene practices should always be followed.
Eye Protection	No special eye protection is necessary.
Body Protection	Normal work wear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State
Colour
Odour
рН
Boiling Range/Point (⁰ C)
Flash Point (PMCC) ((^o C)
Solubility in Water (kg/m ³)
Density (kg/m³)
Viscosity (CST) 40 ⁰ C

Liquid Amber Faint N/A N/A EXCEEDS 210 Insoluble 0.874 – 0.885 ISO VG 32,46,68,100,150 &220 Grade

10. STABILITY AND REACTIVITY

Stability Conditions to Avoid Materials to Avoid Hazardous Decomposition Products Stable under normal conditions Strong oxidation Strong oxidizing agents Combustion will generate carbon monoxide and smoke, possibly thick and choking, resulting in zero visibility.

11.TOXICOLOGICAL INFORMATION

Acute Toxicity

Low order of acute toxicity.

12.ECOLOGICAL INFORMATION

Environmental Effects:

No specific ecotoxicity on this product are available. This product



Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



MATERIAL SAFETY DATA SHEET FLEETLINE CIRCULATING (32,46,68,100,150,220)

may present environmental risks common to oil spills.

13.DISPOSAL

Product Disposal

Container Disposal

Dispose of in accordance with all applicable local and national regulations. An approved drum recycler can recycle containers.

14.TRANSPORT INFORMATION

Un Class	Not classified
IMO Class	Not classified
IMDG Class	Not classified
IATA Class	Not classified

15.REGULATORY INFORMATION

Government Inventory Status	Not established.
US Superfund Amendments	This product contains no "Extremely Hazardous Substances"
	Respirators must follow as 1715/1716 standard for approved
	respirators and NZSS 2209/2266 standards.

16.OTHER INFORMATION

MSDS Issue:	16 June 2018
MSDS Data Revision date:	01 May 2020
Product Use:	Anti Wear Circulating oil.

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.

PREPARED BY:

TECHNICAL SERVICES / LUBRICANTS MARKETING DEPT FLEETLINE, OILFLOW CC.

