Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



MATERIAL SAFETY DATA SHEET Fleetline UHVI Hydraulic 46

1. PRODUCT AND COMPANY IDENTIFICATION

| Trade Name | FLEETLINE UHVI HYDRAULIC 46 |
|-----------------------|-----------------------------|
| Manufacturer/Supplier | OILFLOW cc |
| | P.O.Box 14527 |
| | 562 Crocker Road |
| | Wadeville |
| | 1422 |
| Phone Number | (011) 827-5848 |
| Fax Number | (011) 827-5832 |

2. COMPOSITION/INFORMATION ON THE COMPONENTS Hazardous Components in Product

| Pure substance/ Mixture | Mixture |
|-----------------------------|---------|
| SOLVENT REFINED MINERAL OIL | > 94% |
| Additives package | < 6% |

3. HAZARD IDENTIFICATION WARNING STATEMENTS:

- Avoid prolong or repeated, contact with used motor oil.
- If skin contact occurs wash exposed areas with soap and water launder contaminated clothing.

| Main Hazards | Not hazardous according to OSHA 29 CFR 1910.1200 |
|-----------------------------|---|
| Health Effects – Eyes | Not expected to cause eye irritation. |
| Health Effects – Skin | Expect to cause no more than minor skin irritation. |
| | Prolong or Frequently repeated contact may cause |
| | more severe irritation or may cause the skin to |
| | become racked or dry from defatting action of the material. |
| Health Effects – Inhalation | May cause irritation, dizziness or nausea if inhaled over a prolonged period, especially whilst hot |
| Health Effects - Oral | If more than several mouthfuls are swallowed, abdominal discomfort, nausea, and diarrhoea my occur. |

4. FIRST AID MEASURES

First Aid – Eyes

First Aid – Skin First Aid – Ingestion Flush thoroughly with water. If irritation occurs, call a doctor. Wash skin with soap and water. If swallowed and person is conscious, give water or milk. Do not



Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



MATERIAL SAFETY DATA SHEET Fleetline UHVI Hydraulic 46

make person vomit except on advice of medical personnel. If advice cannot be obtained, take person and container (or label) to nearest emergency treatment centre, never give anything by mouth to unconscious person. Remove from exposure and if the patient experiences irritation,

First Aid – Inhalation

nausea or unconsciousness, seek medical assistance.

5. FIRE FIGHTING MEASURES

Extinguishing Media Unsuitable Extinguishing Media Special Hazards of Product Protective Equip, for Fire-Fighting

Igniting temperature Flammable limits Flash Point Long term toxic Use foam, dry chemical, carbon dioxide or water fog. Do not use water jet. No special hazards. Wear self-contained breathing apparatus for fires in enclosed spaces. N/A N/A 210 - 240°C The base oil components are not expected to be carcinogenic based on IARC criteria. This product has not been tested for chronic health effects.

6. ACCIDENTAL RELEASE MEASURES

| Personal Precautions | Material can create slippery conditions underfoot. |
|---------------------------|---|
| Environmental Precautions | Try to prevent the material from entering drains or watercourses. |
| Spillages | Contain and absorb using diatomaceous earth or other inert |
| | material. Transfer into suitable containers for disposal. |

7. HANDLING AND STORAGE

| Handling | No special precautions are required. | |
|----------|---|--|
| Storage | Storage temperature should be controlled to between 1 and 40°C. | |
| | Where outside storage of drums is unavoidable, they should be | |
| | stored horizontally to avoid ingress of water. | |

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Standards OIL MIST, CHEMICAL

UK EH40: OES 5mg/m³ 8 h TWA. UK EH40: OES 10mg/m³ 15 min TWA.



Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



MATERIAL SAFETY DATA SHEET Fleetline UHVI Hydraulic 46

| Engineering Control Measures | Exposure to this material may be controlled in a number of ways. The measures appropriate for a particular worksite depend on how the material is used and on the potential for exposure. Use of the basic principles of industrial Hygiene will enable this material to be used safely. |
|------------------------------|--|
| Respiratory Protection | Respiratory protection is not normally required. |
| Hand Protection | No special protection needed. However, good personal hygiene practices should always be followed. |
| Eye Protection | No special eye protection is necessary. |
| Body Protection | Normal work wear. |

9. PHYSICAL AND CHEMICAL PROPERTIES

| Physical State | Liquid |
|---------------------------------------|-----------|
| Colour | Amber |
| Odour | Faint |
| рН | N/A |
| Boiling Range/Point (⁰ C) | N/A |
| Flash Point (PMCC) (^o C) | >210 |
| Solubility in Water (kg/m³) | Insoluble |
| Density (kg/m³) @20 ^o C | 0.875 |
| Viscosity (cSt) @40 °C | 46 |
| | |

10. STABILITY AND REACTIVITY

| Stability | Stable under normal conditions |
|----------------------------------|--|
| Conditions to Avoid | Strong oxidation |
| Materials to Avoid | Strong oxidizing agents |
| Hazardous Decomposition Products | Combustion will generate carbon monoxide and smoke, possibly |
| | thick and choking, resulting in zero visibility. |

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Low order of acute toxicity.

12. ECOLOGICAL INFORMATION

Environmental Effects:

No specific ecotoxicity on this product are available. This product may present environmental risks common to oil spills.



Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



MATERIAL SAFETY DATA SHEET Fleetline UHVI Hydraulic 46

13. DISPOSAL

| Product Disposal | Dispose of in accordance with all applicable local and national |
|--------------------|---|
| | regulations. |
| Container Disposal | An approved drum recycler can recycle containers. |

14. TRANSPORT INFORMATION

| Un Class | Not classified |
|------------|----------------|
| IMO Class | Not classified |
| IMDG Class | Not classified |
| IATA Class | Not classified |

15. REGULATORY INFORMATION

| Government Inventory Status | Not established. | |
|-----------------------------|--|--|
| US Superfund Amendments | This product contains no "Extremely Hazardous Substances" | |
| | Respirators must follow as 1715/1716 standard for approved | |
| | respirators and NZSS 2209/2266 standards. | |

16. OTHER INFORMATION

| MSDS Issue: | 16 June 2018 |
|--------------------------|-------------------------------|
| MSDS Data Revision date: | 01 May 2020 |
| Product Use: | Anti Wear UHVI Hydraulic Oil. |

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.

PREPARED BY:

TECHNICAL SERVICES

