

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline Industrial Gear Oil 220

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: FLEETLINE INDUSTRIAL GEAR 220
Manufacturer/Supplier: OILFLOW cc
P.O. Box 14527
562 Crocker Road, Wadeville, Germiston, South Africa
1422
Health Emergency Telephone: 011 827 5848
Oilflow Website: www.oilflow.co.za

2. COMPOSITION/INFORMATION ON THE COMPONENTS

Hazardous Components in Product

| Component Name | Concentration | R Phrases | Classification |
|-----------------------------|---------------|-----------|----------------|
| Solvent refined mineral oil | 98.00 – 99.00 | | |
| Performance agents | 1.00 - 2.00 | | |

3. HAZARD IDENTIFICATION

| | |
|-----------------------------|--|
| Main Hazards | Not hazardous according to OSHA 29 CFR 1910.1200 |
| Health Effects – Eyes | May cause irritation to the eyes. |
| Health Effects – Skin | No hazard providing normal cleansing is carried out. |
| Health Effects – Ingestion | No problems expected for minor ingestion. However, for amounts exceeding ½ litre give 1 or 2 glasses of water and call a doctor. |
| Health Effects – Inhalation | May cause irritation, dizziness or nausea if inhaled over a prolonged period, especially whilst hot. |

4. FIRST AID MEASURES

| | |
|------------------------|---|
| First Aid – Eyes | Flush thoroughly with water. If irritation occurs, call a doctor. |
| First Aid – Skin | Wash skin with soap and water. |
| First Aid – Ingestion | Wash out mouth with water. Obtain medical attention. Do Not induce vomiting. |
| First Aid – Inhalation | Remove from exposure and if the patient experiences irritation, nausea or unconsciousness, seek medical assistance. |

5. FIRE FIGHTING MEASURES

Extinguishing Media Use foam, dry chemical, carbon dioxide or water fog.



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline Industrial Gear Oil 220

Unsuitable Extinguishing Media
Special Hazards of Product
Protective Equip, for Fire-Fighting

Do not use water jet.
No special hazards.
Wear self-contained breathing apparatus for fires in Enclosed spaces.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions
Environmental Precautions
Spillages

Material can create slippery conditions underfoot.
Try to prevent the material from entering drains or watercourses.
Contain and absorb using diatomaceous earth or other inert material. Transfer into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling
Storage

No special precautions are required.
Storage temperature should be controlled to between 1 and 40°C.
Where outside storage of drums is unavoidable, they should be stored horizontally to avoid ingress of water.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Standards
OIL MIST, CHEMICAL

UK EH40: OES 5mg/m³ 8 h TWA. UK EH40: OES 10mg/m³ 15 min TWA.

Engineering Control Measures

Exposure to this material may be controlled in several ways. The measures appropriate for a worksite depend on how the material is used and on the potential for exposure. Use of the basic principles of industrial Hygiene will enable this material to be used safely.

Respiratory Protection
Hand Protection

Respiratory protection is not normally required.
No special protection needed. However, good personal hygiene practices should always be followed.

Eye Protection
Body Protection

Chemical goggles if there is a risk of eye contact.
Normal work wear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State
Colour
Odour
pH
Boiling Range/Point (°C)
Flash Point (PMCC) (°C)

Liquid
Amber
Faint
N/A
> 320
>200



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline Industrial Gear Oil 220

| | |
|--|-----------|
| Solubility in Water (kg/m ³) | Insoluble |
| Density @20 °C (kg/m ³) | 0.904 |
| Auto-flammability (°C) | > 350 |
| Viscosity @ 40 °C (cSt) | 220 |

10. STABILITY AND REACTIVITY

| | |
|----------------------------------|---|
| Stability | Stable under normal conditions |
| Conditions to Avoid | Strong oxidation |
| Materials to Avoid | Strong oxidizing agents |
| Hazardous Decomposition Products | Combustion will generate carbon monoxide and smoke, possibly thick and choking, resulting in zero visibility. |

11. TOXICOLOGICAL INFORMATION

| | |
|----------------|------------------------------|
| Acute Toxicity | Low order of acute toxicity. |
|----------------|------------------------------|

12. ECOLOGICAL INFORMATION

| | |
|---------------------------|--|
| Mobility | The product will leach into soil and will float on water. |
| Persistence/Degradability | The product is expected to biodegrade very slowly with time. |

13. DISPOSAL

| | |
|--------------------|--|
| Product Disposal | Dispose of in accordance with all applicable local and national regulations. |
| Container Disposal | An approved drum recycler can recycle containers. |

14. TRANSPORT INFORMATION

| | |
|------------|----------------|
| Un Class | Not classified |
| IMO Class | Not classified |
| IMDG Class | Not classified |
| IATA Class | Not classified |

15. REGULATORY INFORMATION

| | |
|-----------------------------|---|
| Labelling information | Irritant |
| Government Inventory Status | Not established. |
| US Superfund Amendments | This product contains no "Extremely Hazardous Substances" |



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline Industrial Gear Oil 220

16. OTHER INFORMATION

| | |
|-------------------|---------------------|
| MSDS First Issued | 01 May 2018 |
| MSDS Data Revised | 01 May 2020 |
| Product Use | Industrial Gear Oil |

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.

PREPARED BY:

TECHNICAL SERVICES

