

PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: [oilflow@oilflow.co.za](mailto:oilflow@oilflow.co.za)  
[www.oilflow.co.za](http://www.oilflow.co.za)



## MATERIAL SAFETY DATA SHEET

### Fleetline Industrial Gear Oil 320

#### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** FLEETLINE INDUSTRIAL GEAR 320  
**Manufacturer/Supplier:** OILFLOW cc  
P.O. Box 14527  
562 Crocker Road, Wadeville, Germiston, South Africa  
1422  
**Health Emergency Telephone:** 011 827 5848  
**Oilflow Website:** [www.oilflow.co.za](http://www.oilflow.co.za)

#### 2. COMPOSITION/INFORMATION ON THE COMPONENTS

##### Hazardous Components in Product

Component Name	Concentration	R Phrases	Classification
SOLVENT REFINED MINERAL OIL	98.00 – 99.00		
PERFORMANCE AGENTS	1.00 - 2.00		

#### 3. HAZARD IDENTIFICATION

Main Hazards	Not hazardous according to OSHA 29 CFR 1910.1200
Health Effects – Eyes	May cause irritation to the eyes.
Health Effects – Skin	No hazard providing normal cleansing is carried out.
Health Effects – Ingestion	No problems expected for minor ingestion. However, for amounts exceeding ½ litre give 1 or 2 glasses of water and call a doctor.
Health Effects – Inhalation	May cause irritation, dizziness or nausea if inhaled over a prolonged period, especially whilst hot.

#### 4. FIRST AID MEASURES

First Aid – Eyes	Flush thoroughly with water. If irritation occurs, call a doctor.
First Aid – Skin	Wash skin with soap and water.
First Aid – Ingestion	Wash out mouth with water. Obtain medical attention. Do Not induce vomiting.
First Aid – Inhalation	Remove from exposure and if the patient experiences irritation, nausea or unconsciousness, seek medical assistance.

#### 5. FIRE FIGHTING MEASURES

Extinguishing Media Use foam, dry chemical, carbon dioxide or water fog.



PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## MATERIAL SAFETY DATA SHEET

### Fleetline Industrial Gear Oil 320

Unsuitable Extinguishing Media  
Special Hazards of Product  
Protective Equip, for Fire-Fighting

Do not use water jet.  
No special hazards.  
Wear self-contained breathing apparatus for fires in Enclosed spaces.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions  
Environmental Precautions  
Spillages

Material can create slippery conditions underfoot.  
Try to prevent the material from entering drains or watercourses.  
Contain and absorb using diatomaceous earth or other inert material. Transfer into suitable containers for disposal.

#### 7. HANDLING AND STORAGE

Handling  
Storage

No special precautions are required.  
Storage temperature should be controlled to between 1 and 40°C.  
Where outside storage of drums is unavoidable, they should be stored horizontally to avoid ingress of water.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Standards  
OIL MIST, CHEMICAL

UK EH40: OES 5mg/m<sup>3</sup> 8 h TWA. UK EH40: OES 10mg/m<sup>3</sup> 15 min TWA.

Engineering Control Measures

Exposure to this material may be controlled in several ways. The measures appropriate for a worksite depend on how the material is used and on the potential for exposure. Use of the basic principles of industrial Hygiene will enable this material to be used safely.

Respiratory Protection  
Hand Protection

Respiratory protection is not normally required.  
No special protection needed. However, good personal hygiene practices should always be followed.

Eye Protection  
Body Protection

Chemical goggles if there is a risk of eye contact.  
Normal work wear.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State  
Colour  
Odour  
pH  
Boiling Range/Point (°C)  
Flash Point (PMCC) (°C)

Liquid  
Amber  
Faint  
N/A  
> 320  
>200



PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## MATERIAL SAFETY DATA SHEET

### Fleetline Industrial Gear Oil 320

Solubility in Water (kg/m <sup>3</sup> )	Insoluble
Density @20 °C (kg/m <sup>3</sup> )	0.911
Auto-flammability (°C)	> 350
Viscosity @ 40 °C (cSt)	320

#### 10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions
Conditions to Avoid	Strong oxidation
Materials to Avoid	Strong oxidizing agents
Hazardous Decomposition Products	Combustion will generate carbon monoxide and smoke, possibly thick and choking, resulting in zero visibility.

#### 11. TOXICOLOGICAL INFORMATION

Acute Toxicity	Low order of acute toxicity.
----------------	------------------------------

#### 12. ECOLOGICAL INFORMATION

Mobility	The product will leach into soil and will float on water.
Persistence/Degradability	The product is expected to biodegrade very slowly with time.

#### 13. DISPOSAL

Product Disposal	Dispose of in accordance with all applicable local and national regulations.
Container Disposal	An approved drum recycler can recycle containers.

#### 14. TRANSPORT INFORMATION

Un Class	Not classified
IMO Class	Not classified
IMDG Class	Not classified
IATA Class	Not classified

#### 15. REGULATORY INFORMATION

Labelling information	Irritant
Government Inventory Status	Not established.
US Superfund Amendments	This product contains no "Extremely Hazardous Substances"



PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## MATERIAL SAFETY DATA SHEET

### Fleetline Industrial Gear Oil 320

---

#### 16. OTHER INFORMATION

MSDS First Issued	01 May 2018
MSDS Data Revised	01 May 2020
Product Use	Industrial Gear Oil

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.

PREPARED BY:

TECHNICAL SERVICES

