Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



MATERIAL SAFETY DATA SHEET Fleetline Needle Oil

1. PRODUCT AND COMPANY IDENTIFICATION

Trade Name

Oilflow Website:

Manufacturer/Supplier

Health Emergency Telephone

FLEETLINE Needle Oil OILFLOW cc 562 Crocker Road, Wadeville, Germiston, South Africa 1422 011 827 5848 www.oilflow.co.za

2. COMPOSITION/INFORMATION ON THE COMPONENTS

Hazardous Components in Product

Component Name	Concentration	R Phrases	Classification
Solvent refined mineral oil	100.00		

3. HAZARD IDENTIFICATION

Main Hazards	Not hazardous according to OSHA 29 CFR 1910.1200
Health Effects – Eyes	May cause irritation to the eyes.
Health Effects – Skin	No hazard provided normal cleansing is carried out.
Health Effects – Ingestion	No problems expected for minor ingestion. However, for amounts
	exceeding ½ litre give 1 or 2 glasses of water and call a doctor.
Health Effects – Inhalation	May cause irritation, dizziness or nausea if inhaled over a prolonged period,
	especially whilst hot.

4. FIRST AID MEASURES

First Aid – Eyes	Flush thoroughly with water. If irritation occurs, call a doctor.
First Aid – Skin	Wash skin with soap and water.
First Aid – Ingestion	Wash out mouth with water. Obtain medical attention. Do not induce
	vomiting.
First Aid – Inhalation	Remove from exposure and if the patient experiences irritation, nausea or
	unconsciousness seek medical assistance.



Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



MATERIAL SAFETY DATA SHEET Fleetline Needle Oil

5. FIRE FIGHTING MEASURES

Extinguishing Media	Use foam, dry chemical, carbon dioxide or water fog.
Unsuitable Extinguishing Media	Do not use water jet.
Special Hazards of Product	No special hazards
Protective Equip. for Fire-Fighting	Wear self-contained breathing apparatus for fires in enclosed spaces.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Material can create slippery conditions underfoot.
Environmental Precautions	Try to prevent the material from entering drains or watercourses.
Spillages	Contain and absorb using diatomaceous earth or other inert materials.
	Transfer into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling	No special precautions are required.
Storage	Storage temperature should be controlled to between 1 and 40 $^{\circ}\text{C}.$ Where
	outside Storage of drums is unavoidable; they should be stored
	horizontally to avoid ingress of water.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Standard OIL MIST, MINERAL Engineering Control Measures	 UK EH40: OES 5mg/m³ 8 h TWA. UK EH40: OES 10mg/m³ 15 min TWA. Exposure to this material may be controlled in several ways. The measures appropriate For a worksite depend on how the material is used and on the potential for
exposure.	
	Use of the basic principles of Industrial Hygiene will enable this material to
be used	
	safely.
Respiratory Protection	Respiratory protection is not normally required.
Hand Protection should	No special protection needed. However, good personal hygiene practices
	always be followed.
Eye Protection	Chemical goggles if there is a risk of eye contact.
Body Protection	Normal work wear.



Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



MATERIAL SAFETY DATA SHEET Fleetline Needle Oil

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Colour	Amber
Odour	Faint
рН	N/A
Boiling Range/Point (°C)	Boils above 320
Flash Point (PMCC) (°C)	Exceeds 200
Solubility in Water (kg/m ³)	Insoluble
Density (kg/m³) @20ºC	0.865 -0.883
Auto-flammability (°C)	Above 350
Viscosity @40ºC (cSt)	30 - 110

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions
Conditions to Avoid	Strong oxidation
Materials to Avoid	Strong oxidizing agents
Hazardous Decomposition ProductCombustion will generate carbon monoxide and smoke, possibly thick and	

choking, resulting in zero visibility.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity	Low order of acute toxicity
----------------	-----------------------------

12. ECOLOGICAL INFORMATION

Mobility	The product will leach into soil and will float on water.
Persistence/Degradability	The product is expected to biodegrade very slowly with time.

13. DISPOSAL

Product Disposal	Dispose of in accordance with all applicable local and national regulations.
	The product may also be burned in an enclosed burner.
Container Disposal	An approved drum recycler can recycle containers.

14. TRANSPORT INFORMATION

UN Class

Not classified



Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



MATERIAL SAFETY DATA SHEET Fleetline Needle Oil

IMO Class	Not classified
IMDG Class	Not classified
IATA Class	Not classified

15. REGULATORY INFORMATION

Labelling Information	Irritant
Government Inventory Status	Not established
US Superfund Amendments	This product contains no "Extremely Hazardous Substances"

16. OTHER INFORMATION

MSDS First Issued	01 May 2001
MSDS Data Revised	01 May 2020
Product Use	Needle oil

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.

PREPARED BY:

TECHNICAL SERVICES

