

PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: [oilflow@oilflow.co.za](mailto:oilflow@oilflow.co.za)  
[www.oilflow.co.za](http://www.oilflow.co.za)



## MATERIAL SAFETY DATA SHEET

### Fleetline Rockdrill 150

#### 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Fleetline Rockdrill 150  
**Manufacturer/Supplier:** OILFLOW cc  
P.O. Box 14527  
562 Crocker Road, Wadeville, Germiston, South Africa  
1422  
**Health Emergency Telephone:** 011 827 5848  
**Oilflow Website:** [www.oilflow.co.za](http://www.oilflow.co.za)

#### 2. COMPOSITION/INFORMATION ON THE COMPONENTS

##### Hazardous Components in Product

Component Name	Concentration	R Phrases	Classification
SOLVENT REFINED MINERAL OIL	97.00		
PERFORMANCE AGENTS	3.00		

#### 3. HAZARD IDENTIFICATION

**Main Hazards:** Not hazardous according to OSHA 29 CFR 1910.1200

**Health Effects – Eyes:** May cause irritation to the eyes.

**Health Effects – Skin:** No hazard providing normal cleansing is carried out.

**Health Effects – Ingestion:** No problems expected for minor ingestion. However, for amounts exceeding ½ litre give 1 or 2 glasses of water and call a doctor.

**Health Effects – Inhalation:** May cause irritation, dizziness or nausea if inhaled over a prolonged period, especially whilst hot.

#### 4. FIRST AID MEASURES

**First Aid – Eyes:** Flush thoroughly with water. If irritation occurs, call a doctor.

**First Aid – Skin:** Wash skin with soap and water.



PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## MATERIAL SAFETY DATA SHEET

### Fleetline Rockdrill 150

First Aid – Ingestion	Wash out mouth with water. Obtain medical attention. Do not induce vomiting.
First Aid – Inhalation	Remove from exposure and if the patient experiences irritation, nausea or unconsciousness, seek medical assistance.

#### 5. FIRE FIGHTING MEASURES

Extinguishing Media	Use foam, dry chemical, carbon dioxide or water fog.
Unsuitable Extinguishing Media	Do not use water jet.
Special Hazards of Product	No special hazards.
Protective Equip, for Fire-Fighting	Wear self-contained breathing apparatus for fires in enclosed spaces.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Material can create slippery conditions underfoot.
Environmental Precautions	Try to prevent the material from entering drains or watercourses.
Spillages	Contain and absorb using diatomaceous earth or other inert material. Transfer into suitable containers for disposal.

#### 7. HANDLING AND STORAGE

Handling	No special precautions are required.
Storage	Storage temperature should be controlled to between 1 and 40°C. Where outside storage of drums is unavoidable, they should be stored horizontally to avoid ingress of water.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Standards	
OIL MIST, CHEMICAL	UK EH40: OES 5mg/m <sup>3</sup> 8 h TWA. UK EH40: OES 10mg/m <sup>3</sup> 15 min TWA.



PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## MATERIAL SAFETY DATA SHEET

### Fleetline Rockdrill 150

Engineering Control Measures	Exposure to this material may be controlled in several ways. The measures appropriate for a worksite depend on how the material is used and on the potential for exposure. Use of the basic principles of industrial Hygiene will enable this material to be used safely.
Respiratory Protection	Respiratory protection is not normally required.
Hand Protection	No special protection needed. However, good personal hygiene practices should always be followed.
Eye Protection	Chemical goggles if there is a risk of eye contact.
Body Protection	Normal work wear.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Colour	Amber
Odour	Faint
pH	N/A
Density @ 20°C	0,887
Flash Point (PMCC) (°C)	> 230
Solubility in Water (kg/m <sup>3</sup> )	Insoluble
Viscosity (cSt) @40 °C	150

## 10. STABILITY AND REACTIVITY


Stability	Stable under normal conditions
Conditions to Avoid	Strong oxidation
Materials to Avoid	Strong oxidizing agents
Hazardous Decomposition Products	Combustion will generate carbon monoxide and smoke, possibly thick and choking, resulting in zero visibility.

## 11. TOXICOLOGICAL INFORMATION



PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## MATERIAL SAFETY DATA SHEET

### Fleetline Rockdrill 150

**Acute Toxicity** Low order of acute toxicity.

#### 12. ECOLOGICAL INFORMATION

**Mobility** The product will leach into soil and will float on water.  
**Persistence/Degradability** The product is expected to biodegrade very slowly with time.

#### 13. DISPOSAL

**Product Disposal** Dispose of in accordance with all applicable local and national regulations.  
**Container Disposal** An approved drum recycler can recycle containers.

#### 14. TRANSPORT INFORMATION

**Un Class** Not classified  
**IMO Class** Not classified  
**IMDG Class** Not classified  
**IATA Class** Not classified

#### 15. REGULATORY INFORMATION

**Labelling information** Irritant  
**Government Inventory Status** Not established.  
**US Superfund Amendments** This product contains no "Extremely Hazardous Substances"

#### 16. OTHER INFORMATION

**MSDS First Issued** 01 May 2018  
**MSDS Data Revised** 01 May 2020

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a



PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: [oilflow@oilflow.co.za](mailto:oilflow@oilflow.co.za)  
[www.oilflow.co.za](http://www.oilflow.co.za)



## MATERIAL SAFETY DATA SHEET

### Fleetline Rockdrill 150

---

workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.

PREPARED BY: TECHNICAL SERVICES

