

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline Threadcut Oil

1. PRODUCT AND COMPANY IDENTIFICATION

Trade Name	FLEETLINE THREADCUT OIL
Manufacturer/Supplier	OILFLOW cc P.O.Box 14527 562 Crocker Road, Wadeville, Germiston, South Africa 1422
Phone Number	(011) 827-5848
Fax Number	(011) 827-5832
Oilflow Website:	www.oilflow.co.za

2. COMPOSITION/INFORMATION ON THE COMPONENTS

Hazardous Components in Product

Component Name	Concentration	R Phrases	Classification
Solvent refined mineral oil	84		
Performance agents	16		

3. HAZARD IDENTIFICATION

Main Hazards	Not hazardous according to OSHA 29 CFR 1910.1200
Health Effects – Eyes	May cause irritation to the eyes.
Health Effects – Skin	No hazard provided normal cleansing is carried out.
Health Effects – Ingestion	No problems expected for minor ingestion. However, for amounts exceeding ½ litre. Give 1 or 2 glasses of water and call the doctor
Health Effects Inhalation	May cause irritation, dizziness or nausea if inhaled over a prolonged period especially whilst hot.

4. FIRST AID MEASURES

First Aid – Eyes	Flush thoroughly with water. If irritation occurs, call a doctor.
First Aid – Skin	Wash skin with soap and water.
First Aid – Ingestion	Wash out mouth with water. Obtain medical attention. Do not induce vomiting.
First Aid – Inhalation	Remove from exposure and if the patient experiences Irritation nausea or unconsciousness seek medical help.

5. FIRE FIGHTING MEASURES

Extinguishing Media	Use foam, dry chemical, carbon dioxide or water fog.
Unsuitable Extinguishing Media	Do not use water jet.
Special Hazards of Product	No special hazards



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline Threadcut Oil

Protective Equip. for Fire-Fighting enclosed spaces

Wear self-contained breathing apparatus for fires in

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions
Environmental Precautions

Material can create slippery conditions underfoot. Try to prevent the material from entering drains or watercourses.

Spillages

Contain and absorb using diatomaceous earth or other inert materials. Transfer into suitable containers for disposal.

7. HANDLING AND STORAGE

Handling
Storage

No special precautions are required. Storage temperature should be controlled To between 1 and 40°C. Where outside Storage drums is unavoidable, they should be stored horizontally to avoid ingress of water.

8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

Occupational Exposure Standards
OIL MIST, MINERAL

UK EH40: OES 5mg/m³ 8 h TWA. UK EH40: OES 10mg/m³ 15 min TWA.

Engineering Control Measures

Exposure to this material may be controlled in several ways. The measures appropriate

Respiratory Protection
Hand Protection
hygiene

For a worksite depend on how the material is used and on the potential for exposure. Use of the basic principles of Industrial Hygiene will enable this material to be used safely.

Eye Protection
Body Protection

Respiratory protection is not normally required. No special protection needed. However, good personal

practices should always be followed.

Chemical goggles if there is a risk of eye contact.

Normal work wear.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State
Density (Kg/L) @20°C
Colour

Liquid

0.867

Amber



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline Threadcut Oil

Odour	Faint
pH	N/A
Active Sulphur	2%
Solubility in Water (kg/L)	Insoluble
Viscosity (cSt) @40°C	30

10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions
Conditions to Avoid	Strong oxidation
Materials to Avoid	Strong oxidizing agents
Hazardous Decomposition Products possibly	Combustion will generate carbon monoxide and smoke, thick and choking, resulting in zero visibility.

11. TOXOLOGICAL INFORMATION

Acute Toxicity	Low order of acute toxicity
----------------	-----------------------------

12. ECOLOGICAL INFORMATION

Mobility	The product will leach into soil and will float on water.
Persistence/Degradability	The product is expected to biodegrade very slowly with time

13. DISPOSAL

Product Disposal	Dispose of in accordance with all applicable local and national regulations.
Container Disposal	The product may also be burned in an enclosed burner. An approved drum recycler can recycle containers.

14. TRANSPORT INFORMATION

UN Class	Not classified
IMO Class	Not classified
IMDG Class	Not classified
IATA Class	Not classified



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



MATERIAL SAFETY DATA SHEET

Fleetline Threadcut Oil

15. REGULATORY INFORMATION

Labelling Information
Government Inventory Status
US Superfund Amendments
Substances"

Irritant
Not established
This product contains no "Extremely Hazardous

16. OTHER INFORMATION

MSDS First Issued 01 May 2019
MSDS Data Revised 01 May 2020
Product use Thread cutting Oil

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.

PREPARED BY: TECHNICAL SERVICES

