


PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: [oilflow@oilflow.co.za](mailto:oilflow@oilflow.co.za)  
[www.oilflow.co.za](http://www.oilflow.co.za)



## MATERIAL SAFETY DATA SHEET

### Fleetline Transmission TO4 10

#### 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product Name:</b>	FLEETLINE TRANSMISSION TO4 10
<b>Manufacturer/Supplier</b>	OILFLOW cc 562 Crocker Road, Wadeville, Germiston, South Africa 1422
<b>Health Emergency Telephone</b>	011 827 5848
<b>Oilflow Website:</b>	<a href="http://www.oilflow.co.za">www.oilflow.co.za</a>

#### 2. COMPOSITION/INFORMATION ON THE COMPONENTS

##### Hazardous Components in Product

Component Name	Concentration	R Phrases	Classification
Solvent refined mineral oil	90.00 – 93.00	Asp. Tox. H304	May lead to congestion of airways
Performance agents	7 - 10	Xn	Harmful if swallowed

#### 3. HAZARD IDENTIFICATION

<b>Main Hazards</b>	Not hazardous according to OSHA 29 CFR 1910.1200
<b>Health Effects – Eyes</b>	May cause irritation to the eyes.
<b>Health Effects – Skin</b>	No hazard provided normal cleansing is carried out.
<b>Health Effects – Ingestion</b>	No problems expected for minor ingestion. However, for amounts exceeding ½ litre give 1 or 2 glasses of water and call a doctor.
<b>Health Effects – Inhalation</b>	May cause irritation, dizziness or nausea if inhaled over a prolonged period, especially whilst hot.

#### 4. FIRST AID MEASURES

<b>First Aid – Eyes</b>	Flush thoroughly with water. If irritation occurs, call a doctor.
<b>First Aid – Skin</b>	Wash skin with soap and water.
<b>First Aid – Ingestion</b>	Wash out mouth with water. Obtain medical attention. Do not induce vomiting.
<b>First Aid – Inhalation</b>	Remove from exposure and if the patient experiences irritation, nausea or unconsciousness seek medical assistance.

#### 5. FIRE FIGHTING MEASURES

<b>Extinguishing Media</b>	Use foam, dry chemical, carbon dioxide or water fog.
<b>Unsuitable Extinguishing Media</b>	Do not use water jet.
<b>Special Hazards of Product</b>	No special hazards
<b>Protective Equip. for Fire-Fighting</b>	Wear self-contained breathing apparatus for fires in enclosed spaces.

#### 6. ACCIDENTAL RELEASE MEASURES

<b>Personal Precautions</b>	Material can create slippery conditions underfoot.
<b>Environmental Precautions</b>	Try to prevent the material from entering drains or watercourses.
<b>Spillages</b>	Contain and absorb using diatomaceous earth or other inert materials. Transfer into suitable containers for disposal



PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## MATERIAL SAFETY DATA SHEET

### Fleetline Transmission TO4 10

## 7. HANDLING AND STORAGE

### Handling Storage

No special precautions are required.  
Storage temperature should be controlled to between 1 and 40°C. Where outside storage drums is unavoidable, they should be stored horizontally to avoid ingress of water.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Occupational Exposure Standards OIL MIST, MINERAL Engineering Control Measures

UK EH40: OES 5mg/m<sup>3</sup> 8 h TWA. UK EH40: OES 10mg/m<sup>3</sup> 15 min TWA.  
Exposure to this material may be controlled in a number of ways. The measures appropriate

For a particular worksite depend on how the material is used and on the potential for exposure.

Use of the basic principles of Industrial Hygiene will enable this material to be used safely.

### Respiratory Protection Hand Protection

Respiratory protection is not normally required.

No special protection needed. However, good personal hygiene practices should always be followed

### Eye Protection Body Protection

Chemical goggles if there is a risk of eye contact.

Normal work wear.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Physical State

Liquid

### Colour

Brown

### Odour

Petroleum odour

### pH

N/A

### Boiling Range/Point (°C)

No data

### Flash Point (PMCC) (°C)

Exceeds 210

### Solubility in Water (kg/m<sup>3</sup>)

Insoluble

### Density (kg/m<sup>3</sup>) @20°C

0.876

### Auto-flammability (°C)

Above 350

### Viscosity (cSt) @40°C

40

## 10. STABILITY AND REACTIVITY

### Stability

Stable under normal conditions

### Conditions to Avoid

Strong oxidation

### Materials to Avoid

Strong oxidizing agents

### Hazardous Decomposition Products

Combustion will generate carbon monoxide and smoke, possibly thick and choking,  
resulting in zero visibility.



PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## MATERIAL SAFETY DATA SHEET

### Fleetline Transmission TO4 10

#### 11. TOXICOLOGICAL INFORMATION

Acute Toxicity	Low order of acute toxicity
----------------	-----------------------------

#### 12. ECOLOGICAL INFORMATION

Mobility	The product will leach into soil and will float on water.
Persistence/Degradability	The product is expected to biodegrade very slowly with time.

#### 13. DISPOSAL

Product Disposal	Dispose of in accordance with all applicable local and national regulations.
Container Disposal	The product may also be burned in an enclosed burner. An approved drum recycler can recycle containers.

#### 14. TRANSPORT INFORMATION

UN Class	Not classified
IMO Class	Not classified
IMDG Class	Not classified
IATA Class	Not classified

#### 15. REGULATORY INFORMATION

Labelling Information	Irritant
Government Inventory Status	Not established
US Superfund Amendments	This product contains no "Extremely Hazardous Substances"

#### 16. OTHER INFORMATION

MSDS Issue	24 June 2018
MSDS Revision	01 May 2020
Product Use	Automotive Transmission oil

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.

