

PO Box 14527, Wadeville 1422  
4 Saligna Road  
Boksburg, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## MATERIAL SAFETY DATA SHEET

### WHITE OIL 32, 68

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Trade Name	White Oil 32, 68
Manufacturer/Supplier	OILFLOW CC P.O.Box 1422 4 Saligna Road, Boksburg, South Africa 1422
Phone Number	(011) 827-5848
Fax Number	(011) 827-5832

#### 2. COMPOSITION/INFORMATION ON THE COMPONENTS

##### Hazardous Components in Product

Component Name	Concentration
Hydroprocessed Base Oil	100.00

#### 3. HAZARD IDENTIFICATION

<b>Main Hazards</b>	Not hazardous according to OSHA 29 CFR 1910.1200
<b>Health Effects – Eyes</b>	May cause irritation to the eyes.
<b>Health Effects – Skin</b>	No hazard provided normal cleansing is carried out.
<b>Health Effects – Ingestion</b>	No problems expected for minor ingestion. However, for amounts exceeding ½ Liter give 1 or 2 glasses of water and call a doctor.
<b>Health Effects – Inhalation</b>	May cause irritation, dizziness or nausea if inhaled over a prolonged period, especially whilst hot.

#### 4. FIRST AID MEASURES

<b>First Aid – Eyes</b>	Flush thoroughly with water. If irritation occurs, call a doctor.
<b>First Aid – Skin</b>	Wash skin with soap and water.
<b>First Aid – Ingestion</b>	Wash out mouth with water. Obtain medical attention. Do not induce vomiting.
<b>First Aid – Inhalation</b>	Remove from exposure and if the patient experiences irritation, nausea or unconsciousness seeks medical assistance.



PO Box 14527, Wadeville 1422  
4 Saligna Road  
Boksburg, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## MATERIAL SAFETY DATA SHEET

### WHITE OIL 32, 68

#### 5. FIRE FIGHTING MEASURES

**Extinguishing Media** Use foam, dry chemical, carbon dioxide or water fog.  
**Unsuitable Extinguishing Media** Do not use water jet.  
**Special Hazards of Product** No special hazards  
**Protective Equip. for Fire-Fighting** Wear self-contained breathing apparatus for fires in enclosed spaces.

#### 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions** Material can create slippery conditions underfoot.  
**Environmental Precautions** Try to prevent the material from entering drains or watercourses.  
**Spillages** Contain and absorb using diatomaceous earth or other inert materials.  
Transfer into suitable containers for disposal.

#### 7. HANDLING AND STORAGE

**Handling** No special precautions are required.  
**Storage** Storage temperature should be controlled to between 1 and 40°C. Where outside Storage of drums is unavoidable; they should be stored horizontally to avoid ingress of water.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Standards**  
**OIL MIST, MINERAL** UK EH40: OES 5mg/m<sup>3</sup> 8 h TWA. UK EH40: OES 10mg/m<sup>3</sup> 15 min TWA.  
**Engineering Control Measures** Exposure to this material may be controlled in several ways. The measures appropriate  
For a worksite depend on how the material is used and on the potential for exposure.  
Use of the basic principles of Industrial Hygiene will enable this material to be used safely.  
**Respiratory Protection** Respiratory protection is not normally required.  
**Hand Protection** No special protection needed. However, good personal hygiene practices should always be followed.  
**Eye Protection** Chemical goggles if there is a risk of eye contact.  
**Body Protection** Normal work wear.



PO Box 14527, Wadeville 1422  
4 Saligna Road  
Boksburg, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## MATERIAL SAFETY DATA SHEET

### WHITE OIL 32, 68

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid
Colour	White/ Clear
Odour	Faint
pH	N/A
Boiling Range/Point (°C)	Boils above 320°C
Flash Point (PMCC) (°C)	Exceeds 200°C
Solubility in Water (kg/m <sup>3</sup> )	Insoluble
Density (kg/m <sup>3</sup> )	0.865 & 0.867
Auto-flammability (°C)	Above 350°C
Viscosity @40°C (cSt)	32, 68

#### 10. STABILITY AND REACTIVITY

Stability	Stable under normal conditions
Conditions to Avoid	Strong oxidation.
Materials to Avoid	Strong oxidizing agents.

**Hazardous Decomposition Product** Combustion will generate carbon monoxide and smoke, possibly thick and choking, resulting in zero visibility.

#### 11. TOXICOLOGICAL INFORMATION

Acute Toxicity	Low order of acute toxicity
----------------	-----------------------------

#### 12. ECOLOGICAL INFORMATION

Mobility	The product will leach into soil and will float on water.
Persistence/Degradability	The product is expected to biodegrade very slowly with time.

#### 13. DISPOSAL

Product Disposal	Dispose of in accordance with all applicable local and national regulations. The product may also be burned in an enclosed burner.
Container Disposal	An approved drum recycler can recycle containers.

#### 14. TRANSPORT INFORMATION

UN Class	Not classified.
----------	-----------------



PO Box 14527, Wadeville 1422  
4 Saligna Road  
Boksburg, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## MATERIAL SAFETY DATA SHEET WHITE OIL 32, 68

---

<b>IMO Class</b>	Not classified.
<b>IMDG Class</b>	Not classified.
<b>IATA Class</b>	Not classified.

### 15. REGULATORY INFORMATION

<b>Labelling Information</b>	Irritant
<b>Government Inventory Status</b>	Not established.
<b>US Superfund Amendments</b>	This product contains no "Extremely Hazardous Substances".

### 16. OTHER INFORMATION

<b>MSDS First Issued</b>	01 May 2001
<b>MSDS Data Revised</b>	01 May 2020
<b>Product Use</b>	White Oil

To the best of our knowledge, the information contained herein is accurate. Although certain hazards may be described we cannot predict that these are the only hazards, or combination of hazards, that may exist in a workplace. This MSDS, therefore, forms a component only of a risk assessment carried out by, or on behalf of, the user.

