

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET

Fleetline Compressor 32/46/68/100

PRODUCT DESCRIPTION

Fleetline Compressor oil is a range of premium quality products blended using highly refined virgin base oils. They contain a balanced additive package consisting of anti-wear, anti-rust, anti-oxidant and anti-foam additives to give outstanding levels of performance and wear protection. They are for use in reciprocating air compressors.

BENEFITS

- Outstanding overall performance
- Extended service intervals
- Excellent oxidation resistance
- Excellent corrosion inhibitors

APPLICATION

Fleetline compressor oils may be used in any air compressor. They promote efficient, economical and safe operations in compressors of all types.

KEY PROPERTIES

ISO GRADE	32	46	68	100
Density @20°C	0.865	0.872	0.877	0.880
Viscosity 40 °C	32	46	68	100
Viscosity 100 °C	5	7	8	8.9
Viscosity Index	96	96	96	96
Flash point C.O.C.	207	210	215	220
Colour	Amber	Amber	Amber	Amber



PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET

Fleetline Compressor 32/46/68/100

PACKAGE SIZE	500ml	1Litre	5 Litres	20 Litres	210 Litres	1000 Litres
Compressor 32	-	-	-	✓	✓	-
Compressor 46	-	✓	✓	✓	✓	✓
Compressor 68	✓	✓	✓	✓	✓	-
Compressor 100	-	-	-	✓	-	-

