

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET

Fleetline Heat Transfer 32,100

PRODUCT DESCRIPTION

Heat transfer oil is a mineral based heat transfer fluid used in enclosed circulating systems for the transfer of heat. It has good oxidation and thermal stability without the use of antioxidants.

APPLICATION

- Heating of domestic and industrial premises.
- Production of steam and hot water.
- Air conditioning.
- Temperature control for storage bins.
- Heating by heat exchange.
- All types of systems (piping, pumps, etc...).
- Heating of heat treatment baths, autoclaves, reaction vessels, furnaces.
- tunnel driers, injection moulding machines, etc...
- all manufacturing processes including cement works, paper mills, timber industry, etc...

BENEFITS

- Non-additive mineral oil
- Good oxidation and thermal stability

KEY PROPERTIES

ISO GRADE	32	100
Viscosity @40°C	32	100
Viscosity @ 100°C	5	12
Viscosity index	100	100
Density @ 20°C	0.861	0,880
Total acid number	0.01	0.03

PACKAGE SIZE	20 Litres	210 Litres
Heat Transfer Oils	✓	✓

