

PO Box 14527, Wadeville 1422
562 Crocker Road
Wadeville, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET

Fleetline Rockdrill Oil

PRODUCT DESCRIPTION

ROCKDRILL OIL is a range of extreme pressure rockdrill oils designed for use in all types of rock drilling such as in mining and construction. The additives used in the formulation give good wear protection coupled with excellent corrosion resistance and excellent surface adhesion properties. It is also suitable for use in a jack hammer.

BENEFITS

- Good wear protection
- Excellent corrosion protection
- Resistant to water washout
- Excellent adhesive and cohesive properties

APPLICATIONS

ROCKDRILL OILS may be used on any type of pneumatic rockdrill. They give good wear protection to the components and provide excellent anti-corrosion properties.

KEY PROPERTIES

ISO Grade	100	150	220	320	460
DENSITY@20 °C	0.885	0.887	0.895	0.899	0.901
Viscosity @40 °C	100	150	220	320	460
Flash Point, °C	230	240	245	250	265

PACKAGE SIZE	20 Litres	210 Litres
Rockdrill oil	✓	✓

