

PO Box 14527, Wadeville 1422  
4 Saligna Road  
Boksburg, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## TECHNICAL DATA SHEET FLEETLINE SLIDWAY OIL 46

### PRODUCT DESCRIPTION

Slidway Oil 46 is a range product designed for use on the slides and ways of metalworking machines. It contains additives to help prevent stick/slip as well as those to ensure that the product stays in place on the slides and ways.

### BENEFITS

- Adheres to guides and slides
- Prevents stick/slip

### APPLICATION

- Slidway Oil may be used on any metalworking machine that has slides and ways that require a lubricant.
- It helps prevent stick/slip from happening, thus assisting in the productions of good surface finishing.
- The tackiness of Slidway Oil ensures that it does not drip off and the ISO 220 grade can be applied to vertical slides and ways.

### TECHNICAL DATA

ISO Grade	46
Viscosity 40 °C	46
Viscosity 100 °C	7.6
Viscosity Index	104
Density @ 40°C	0.869
Flash point C.O.C.	218

PACKAGE SIZE	5 Litres	20 Litres	210 Litres
Slidway oil 46	✓	✓	✓

