PO Box 14527, Wadeville 1422 562 Crocker Road Wadeville, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



TECHNICAL DATA SHEET Fleetline Slideway Oils

PRODUCT DESCRIPTION

Slideway Oil is a range product designed for use on the slides and ways of metalworking machines. It contains additives to help prevent stick/slip as well as those to ensure that the product stays in place on the slides and ways.

BENEFITS

- Adheres to guides and slides
- Prevents stick/slip

APPLICATION

- Slideway Oil may be used on any metalworking machine that has slides and ways that require a lubricant.
- It helps prevent stick/slip from happening, thus assisting in the productions of good surface finishing.
- The tackiness of Slideway Oil ensures that it does not drip off and the ISO 220 grade can be applied to vertical slides and ways.

TECHNICAL DATA

ISO Grade	32	68	220
Viscosity 40 °C	32	68	220
Viscosity 100 °C	5.5	8.7	18.7
Viscosity Index	95	95	95
Density @ 40°C	0.865	0.880	0.895
Flash point C.O.C.	230	230	230

PACKAGE SIZE	5 Litres	20 Litres	210 Litres
Slideway oils	1	1	~

