

PO Box 14527, Wadeville 1422
4 Saligna Road
Boksburg, Johannesburg

Tel: (011) 827-5848
Fax: (011) 827-5832
E-mail: oilflow@oilflow.co.za
www.oilflow.co.za



TECHNICAL DATA SHEET FLEETLINE THREADCUT

PRODUCT DESCRIPTION

Threadcut is a premium quality extreme pressure neat cutting oil manufactured from blends of essentially solvent refined minerals and selected additives for medium to high severity cutting operations on a variety of ferrous metals.

BENEFITS

- Extended machining performance
- High production levels
- Controlled extreme pressure properties.
- Good tool life
- Higher speeds and feeds may be used.
- Excellent surface finish
- Versatile in many applications
- Low misting and smoking potential

APPLICATIONS

- Threadcut can be used on all ferrous metals. It will not stain copper alloys, ferrous metals, or copper.
- Threadcut can be used in all general metal removal operations where tool life surface finish and machine tool lubrication are required.

KEY PROPERTIES

Viscosity @ 40°C	24 cSt
Colour	Clear
Density @20°C	0.875 Kg/L

PACKAGE SIZE	5 Litres	20 Litres
Threadcut oil	✓	✓

OVERVIEW

As with all metal working fluids, good housekeeping and systems maintenance are important to ensure the satisfactory working life of the product.

