

PO Box 14527, Wadeville 1422  
562 Crocker Road  
Wadeville, Johannesburg

Tel: (011) 827-5848  
Fax: (011) 827-5832  
E-mail: oilflow@oilflow.co.za  
www.oilflow.co.za



## TECHNICAL DATA SHEET

### Fleetline Vacuum Pump Oil

#### PRODUCT DESCRIPTION

Oilflow vacuum pump oil is formulated using selected additive package with excellent demulsibility properties to provide good resistance to oil degradation even in the presence of moisture. This helps the oil provide a long service life as well as reducing the tendency for sludge build up and varnish formation.

#### APPLICATIONS

- Suitable for applications where ambient temperatures between 0°C and 100°C.
- It is not recommended for use when corrosive gases or chemical vapors are involved in the extraction process.
- Suitable for use in many rotaries and sliding vane vacuum pumps to provide medium/ low vacuum pressures.

#### BENEFITS

- Use of low vapor pressure base oils with a narrow boiling range enables the pump to efficiently work at the vacuum for which it is designed.

#### KEY PROPERTIES

ISO VG		46
VISCOSITY@40 °C	cSt	46
VISCOSITY@100 °C	cSt	6.6
DENSITY @20 °C	Kg/l	0.875
Flash point	°C	230
Pour point	°C	-33

PACKAGE SIZE	5 Litres	20 Litres
Vacuum Pump Oil	✓	✓

