PO Box 14527, Wadeville 1422 4 Saligna Road Boksburg, Johannesburg

Tel: (011) 827-5848 Fax: (011) 827-5832 E-mail: oilflow@oilflow.co.za www.oilflow.co.za



TECHNICAL DATA SHEET FLEETLINE WOOD PLATE

PRODUCT DESCRIPTION

A general-purpose wood preservative oil for exterior out of ground contact applications. It is a deeply penetrating oil that utilises an ultra- violet, stable fungicide that protects and directly reduces the effect of mould and decay. It contains water repelling properties that prevent absorption of water deep into the timber reducing excessive warping, cupping, and splitting of timber. It can resist outdoor weathering for years, even on cracked, old and weathered wood. It is most suited for use with untreated hard woods in various applications such as timber, decks, fences, landscaping, wharves, and bridges.

APPLICATIONS

- Fleetline Wood Plate must be used as supplied, never add anything, or alter in any way.
- Shake well before and during use.
- Fleetline Wood Plate can be applied by brush, roller, or spray. For exterior applications two coats are generally recommended with particular attention to end grain, joints, and interfaces.

BENEFITS

- Non film forming so will not peel or flake.
- Provides a more natural, vibrant, and lively oiled look than traditional oil stains, when freshly coated.
- Offers good water-repellent qualities.
- Requires minimal surface preparation.
- Inhibits moss and mould growth.
- Easy to maintain.
- Reduces the potential for warp, twist, cup, surface checking and splitting

